

GENERAL MOTORS CORPORATION

EXECUTIVE ORDER A-006-1037-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP			VEHICLE TYPE PC=passenger car; LDT=light-dut MDV=medium-duty vehicle; LVW= vehicle weight; ALVW=adjusted	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200		2GMXT04.3186			LDT: 0-3,750 pounds LV	LEV			100K / 100K Gasoline					
No.		ORATIVE Y (EVAF)		No	SPECIAL FEATURES & *= not app			* = not applicabl	e OC	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S				
1	2GMXE	E009	5904	- 1	SFI, WUTWC,	SFI, WUTWC, TWC, 2HO2S, HO2S, OBD (F)					ensor/heated AFS_EGR=exhaust			
2		*			*					gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger				
3		•			*									
4		•				+		dia	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series					
EVAF No.	1	ECS ENGINE VEHICLE VEHI No. SIZE (L) MAKES & MODELS STAN		IICLES SUBJECT TO SFTP			ABBREVIATIONS: *							
1							Chevrolet S10 Pickup 2WD; GMC Sonoma 2WD							
*	*		*		*									
*	*		*											
*	* *		*			*								

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET NA AVERAGE [g/mi]			NMOG @ RAF=0.94 CH4 RAF = *		CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram											
CER	CERT STD		NMOG NMHC		NMHC STD	mg=millig	DE-SOAK K	L [g/mi]=rur	nning loss 000 miles	ORVR	[g/gallor	i dispensed]=	=on-board r	efueling var	or recovery deral test pr	a=aram	
0.06	9	0.068	CERT [g/mi]	CERT [g/mi]	[g/mi] 0.075		CO [g/mi]		x [g/mi]	x [g/mi] HCH		mg/mi]	PM [g/mi]		Hwy NO		
* 0.020 to 0.00 (0.00 to 0.00			[g/iii]	[g/iii]		1.4	STD	CERT	STI	D (CERT	STD	CERT	STD *	CERT	STD	
104		@ 50K	0.053	*			3.4	0.2	0.2	2	1	15	*		0.1	0.3	
		@ UL	0.053	*	0.090	1.4	4.2	0.2	0.3	3	1	18	*	*	0.1	0.4	
400	@ 50	°F & 4K	*	*	*	*	*	*	•		*	*	*	*	*	*	
CO [@ 20	°F&	[= @ 4K (SUL EV) or 50K (T	NMHC+NO (comp	(comp	omposite) [g/mi] [C+NOx [US06]			NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]				
50	50K		SFTP 2 = @ UL (Tier		CERT	STD	CERT	STD	CERT	STD	CE	RT STD	CER	T STD	CERT	STD	
CERT	4.0	1.03	10.0	SFTP 1	*	*	*		*	•	-	•	*	*	*	*	
STD	10.0	4.2		SFTP 2	*	*	*	*	*	*	•	*	*		+	*	
@ UL			ATIVE FAM		EVAPORATIVE FAMILY 2 EVAPO					PORAT	ORATIVE FAMILY 3			EVAPORATIVE FAMILY 4			
0 0 -	3-D	2-[RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR		2-D	RL	ORVR	
CERT	0.9	1.8	0.00	*	*	*	*	*	*	*	*	•	*	*	*	*	
STD	2.0	2.5	0.05	*	*	•	*	*	•	*	-	*	*	*	+	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 29F

R. B. Summerfield, Chief

Mobile Source Operations Division