



## **VOLKSWAGEN AG**

EXECUTIVE ORDER A-007-0227 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

	MODEL TES			JP	M	VEHICLE TYPE C=passenger car; LDT=jight-duty truck; DV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	CATEGOR' vehicle; 1	EMISSION STANDA Y (LEV=low emiss [LEV= transitional LEV; LEV; SULEV=super ULI	ion EVAPORATIVE USEFUL LIFE	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)				
200	2	2VWXV04.0229				PC		LEV	100K / 100K	Gasoline				
No.		VAPORATIVE AMILY (EVAF)		No.	SPECIAL FEATURES EMISSION CONTROL SYSTEM		* = not applicable	OC/TWC=oxidizing/3-wa	y cat. ADSTWC=adsorbing TWC /HO2S=oxygen sensor/heated O2S					
1	2VW	VXR01	R0140234			2TWC, 2HO2S(2),	AIR, SFI, OBD	(F)	AFS/HAFS=air-fuel ratio	sensor/heated AFS_EGR=exhaust				
2		•			2	*		gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFUSFI= multiport fue injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger   CAC=charge air cooler OBD (F) / (P)=full /partial on-board   clagnostic prefix 2=parallel (2) suffix-series						
3					3	•								
4		•			4	*								
EVAI No.			ENG!					ECT TO SFTP E UNDERLINED	ABBREVIATIONS:					
1	1		4.0		$\top$	VOL	KSWAGEN P	ASSAT W8 4MOTIO	SEDAN / WAGON					
*		• "				•								
*		•				•								
•	_ [_	*				*								

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	OG FL RAGE			RAF=0,94 AF = *	NMOG or	nitrogen	HCHO≃for	maldehyde	PM=par	ticulate m	natter R	4 hydrocart AF≖reactivi	v adjustme	nt factor	2/3 D (a/test	l=2/3 dav	
CER	Т	STD	NMOG	NMHC	NMHC STD	mg=milligi	ot-soak Ki ram mi≖	. [g/ml]=ru mile K=1	กกเกg loss 1000 miles			lispensed)= hrenheit			or recovery derai test pr		
0.06	1	0.068	CERT	CERT	[g/mi]	CO [g/mi]		NC	x [g/mi]				PM [g/mi]		Hwy NOx [g/mi]		
0.00	· · · · · · · · · · · · · · · · · · ·		[g/mi]	[g/mi]	191	CERT	STD	CERT	r sti	D CI	ERT	STD	CERT	STD	CERT	STD	
		@ 50K	0.023	•	0.075	1.0	3.4	0.1	0.2	2	1	15	*	*	0.02	0.3	
	@ Or		0.028	•	0.090	1.1	4.2	0.1	0.3	3	1	18	•	•	0.02	0.4	
	@ 50°	°F & 4K	0.043	•	0.150	1.2	3,4	0.1	0.2	2	1	30	•	•	*	*	
	CO [g/mi] @ 20°F & 50K		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			0x [g/mi] osite)			NMHC+NOx [g/mi] [US06]					C+NOx	CO [g/mi] [SC03]		
50			= @ UL (Tier	1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CER	T STD	CERT	STD	CERT	STD	
CERT	1.9	40.00		SFTP 1	•	*	٠	*	0.03	0.14	1.2	8.0	0.12	0.20	1.8	2.7	
STD	10.0	24		SFTP 2	*	•	*	•	•		•	•	•	•	•	•	
@ UL	E	VAPOR.	ATIVE FAM	NLY 1	EVAPORATIVE FAMILY 2 EVAPOR					PORATI	RATIVE FAMILY 3			EVAPORATIVE FAMILY 4			
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	
CERT	1.2	1.3	0.00	0.03		•	•	•	•	*	•	•	*	•	*	•	
STD	2.0	2.5	0.05	0.20	•	•		•	*	•	*	•	·	1	•	•	

**BE IT FURTHER RESOLVED:** That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 29 day of March 2002.

Allen Lyons, Chief

New Vehicle / Engine Programs Branch