BAYERISCHE MOTOREN WERKE AG

EXECUTIVE ORDER A-008-0141-1 ger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| 3 | 1 2 | 1 4.4 | | BMW: 540iA Sport Wagon BMW: 745i, 745Li | | | | | | | | |
|-------------|----------------------|-------------------|---|--|-------------------------------|---|--|--|--|--|--|--|
| 1 | 1 | 4.4 | | | | | | | | | | |
| EVAI No. | | ENGINI SIZE (L | | VEHICLE MAKES & MODELS | VEHICLES SUBJ STANDARDS AR | | | | | | | |
| 4 | • | | | / System of the second district of the second | | OBD (F) / OBD (P) = on-board diagnostics; full / partial compilance (prefix) 2 = parallel (2) (suffix) = series | | | | | | |
| 3 | 2BMXR01 | 2BMXR0158E65 | | | * | AIR = secondary air injection PAIR = pulsed AIR MFI = multiport fuel injection SFI = sequential MFI | | | | | | |
| 2 | 2BMXR01 | 36E46 | 2 | 2TWC, 2HAFS, | 2H02S, SFI, AIR, O | EGR = exhaust gas recirculation | | | | | | |
| 1 | 2BMXR01 | MXR0160E39 | | 2WUTWC, 2TWC, | 2HO2S(2), SFI, AIR | oxygen sensor HO2S = heated O2S AFS = air/fue sensor (aka. universal O2S) HAFS = heated AFS | | | | | | |
| No. | EVAPOR. FAMILY (I | | | SPECIAL FEATU EMISSION CONTROL S | | * = not applicable | TWC = 3-way catalytic converter WUTWC = warm-up TWC OC = oxidation catalytic converter O2S = | | | | | |
| 2002 2BM | | XV04.4LEV | | Passenger Car | Low E | mission Vehicle (LEV) | Gasoline | | | | | |
| MODE | | TEST GROUP | | VEHICLE TYPE | | UST EMISSION ARD CATEGORY | FUEL TYPE | | | | | |

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

| NMOG FLEET AVERAGE [g/mi] | | NMOG [g/mi] @ RAF = 0.94 | | CH4 = methane NMOG = non-CH4 organic gases NMHC = non-CH4 hydrocarbons CO = carbon monoxide NOx = oxides of nitrogen HCHO = formaldehyde PM = particulate matter RAF = reactivity adjustment factor | | | | | | | | | | | | |
|------------------------------|----------------------|-----------------------------|-------------|---|-----------|----------------------|----------|---------------------|-------------|----------------------|---------------------------|------------|----------------------|----------|----------------|----------|
| CERT STD | |) | CH4 RAF = * | | CO [g/mi] | | | NOx [g/mi] | | HCHO [mg/mi] | | PM [g/mi] | | | Hwy NOx [g/mi] | |
| 0.061 | 0.061 0.068 | | CERT | STD | CERT STD | | CE | RT | STD | CERT | STD | CER | T S1 | TD D | CERT | STD |
| | @ | 50K | 0.055 | 0.075 | 0.4 | 3.4 | 0. | .1 | 0.2 | 1 | 15 | • | * | | 0.01 | 0.3 |
| K = 1000 miles | @ 1 | 00K | 0.060 | 0.060 0.090 | | 4.2 | 0. | 0.1 | 0.3 | 1 2 | 18 30 | • | • | - | 0.01 | 0.4 |
| | @ 50°F | , 4K | 0.114 | 0.150 | | 3.4 | 0. | | | | | | - | | • | |
| | | | | NOx [g/mi] NMHC+NOx [g/n | | | | CO [g/mi] [US06] | | | NMHC+NOx [g/mi] (SC03) | | CO [g/mi] [SC03] | | | |
| CERT | STE |) | | mile | CERT | STD | CE | RT | STD | CERT | STD | CERT | г ѕт | D | CERT | STD |
| 4.1 | 4.1 10.0 | | | @ 4K | | * | 0. | 0.11 | | 0.5 | 8.0 | 0.11 | 0.2 | 20 | 0.2 | 2.7 |
| F = degree | Fahrenhe | ahrenheit | | @ 100K | * | * | * | | * | * | * | . • | * | • | • | • |
| <u>@</u> | EVAPORATIVE FAMILY 1 | | | | EVA | EVAPORATIVE FAMILY 2 | | | Ε\ | EVAPORATIVE FAMILY 3 | | | EVAPORATIVE FAMILY 4 | | | |
| 100K | 3-D | 2-D | RL | ORVR | 3-D | 2-D | RL | ORVR | 3-D | 2-D | RL | ORVR | 3-D | 2-D | RL | ORVR |
| CERT | 1.7 | 1.8 | 0.03 | 0.04 | 1.1 | 1.9 | 0.03 | 0.10 | 0.6 | 0.5 | 0.03 | 0.03 | * | * | - | |
| STD | 2.0 | 2.5 | 0.0 | 0.20 | 2.0 | 2.5 | 0.05 | 0.20 | 2.0 | 2.5 | 0.05 | 0.20 | * | * | * | |
| 2-D, 3-D [g/ | test] = 2-d | ay, 3-d | lay diurna | and hot-soal | k | RL [g/mi] | = runnin | g loss | | ORVR [g/g | allon of fue | l dispense | d] = on-bo | ard refu | eling vapo | recovery |

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-008-0141 dated September 27, 2001.

Executed at El Monte, California on this ______day of December 2001

R. B. Summerfield, Chief Mobile Source Operations Division