

FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1029 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

	MODEL YEAR TEST GR			VEHICLE TYPE	EXH/ STANI	AUST EMISSION DARD CATEGORY	FUEL TYPE							
2002	2 2FM	XT02.01F5	0-	3750 Pounds Loaded Vehi Light-Duty Truck	cle Weight	Low	Emission Vehicle (LEV)	Gasoline (Indolene)						
No.	EVAPORATIVE FAMILY (EVAP)		No.	SPECIAL FEA	ATURES & L SYSTEMS	(ECS)	* = not applicable	TWC = 3-way catalytic converter WUTWC = warm-up TWC ADSTWC = adsorber TWC OC = oxidation						
1	2FMXE0	15BBE	1		02S(2), EGR,		catalytic converter O2S = ovugen sensor							
2	*		2		*			AIR = secondary air injection PAIR = pulsed AIR						
3	•		3		*		MFI = multiport fuel injection SFI = sequential MFI TC/SC = turbo/super charge CAC = charge air cooler							
4	*		4		*		OBD (F) / OBD (P) = on-board diagnosis; full / partial compliance (prefix) 2 = parallel (2) (suffix) = serie							
EVAF No.	ECS No.	ENGINE SIZE (L		VEHICLE MAKES & MODELS	VEHICI STAND	ES SUBJ ARDS AR	ECT TO SFTP							
1	11	1 2.0		Ford Escape 2WD/4WD										
*	•	* *		#										
*	•	*		*										
*	*						*							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

NMOG FLEET AVERAGE [g/mi]		NMOG [g/mi] @RAF = 1.00		CH4 = methane NMOG = non-CH4 organic gas NMHC = non-CH4 hydrocarbon CO = carbon monoxide NOx = oxides of nitrogen HCHO = formaldehyde PM = particulate matter RAF = reactivity adjustment factor													
CERT	STD			CH4 RAF = *		CO [g/mi]			NOx [g/mi]		HCHO [mg/mi]		Р	PM [g/mi]		Hwy NOx [g/mi]	
0.068	0.068	В	CE	ERT STD		CERT	STD	С	ERT	STD	CERT	STD	CER	r s	TD	CERT	STD
	@ :	50K	0.04	42	0.075	0.7	3.4		0.1	0.2	1	15	*		*	0.1	0.3
K = 1000 miles	@ 10	@ 100K		52	0.090	0.9	4.2	0.1	0.1	0.3	1 *	18	*		*	0.1	0.4
	@ 50°F, 4K		*						*	*				•	*	*	*
	[g/mi] 0°F, 50K			g = gram mg = milligram mi = mile		NMHC+NOx [g/mi] (composite)] NI	NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMHC	NMHC+NOx [g/mi] [SC03]		CO [g/mi] (SC03)	
CERT	STD	STD				CERT	STD	С	ERT	STD	CERT	STD	CERT	s s	TD	CERT	STD
1.3	10.0		198 1980		@ 4K	*	*		*	*	*	*			*	*	*
F = degree	Fahrenhei	ahrenheit		@ 100K		* *			*	*	•	*	*		•	*	*
@ 100K	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2				EV	EVAPORATIVE FAMILY 3			EVAPORATIVE FAMILY 4				
	3-D	2-D		RL	ORVR	3-D	2-D	RL	ORVE	₹ 3 - D	2-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	1.0	0.9	- (0.01	*	*	*	*	•	*		*	•	•	*	*	*
STD	2.0	2.5	1	0.05	*	*	*	*	•	*	*	*	*	*	*		•
2-D, 3-D [g/	/test] = 2-da	ay, 3-d	ay diu	rnal ar	nd hot-soak		RL [g/mi]	= runni	ng loss		ORVR [g/ga	illon of fue	l dispensed	d] = on-bo	ard refu	eling vapo	r recovery

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 2/57

_ day of June 2001.

R. B. Summerfield, Chief

Mobile Source Operations Division