



## FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1053-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA					M	VEHICLE TYPE C=passenger car; LDT=light-duty truck DV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	CATEGOR vehicle;	EMISSION STANDAY (LEV=low emis LEV= transitional LEV LEV; SULEV=super UL	sion	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200	2002 2FMXT05.4RP5					MDV: 5,751-8,500 pounds ALVW		SULEV		120K / 120K CNG					
No.		VAPORATIVE MILY (EVAF)			No.	SPECIAL FEATURES EMISSION CONTROL SYST		* = not applicable	e OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TW WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O						
1	2FM	2FMXR0000ZYK			1	2TWC, TWC, 2H	O2S, SFI, OBD	AFS	AFS/HAFS=air-fuel ratio sensor/heated AFS_EGR=exhaust						
2		*				2TWC(2), TWC, 2	HO2S, SFI, OB	MAIR	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI						
3		•			3		*	TBI:	TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
4		•			4		*	diag							
EVAI No.			ENGI SIZE					ECT TO SFTP E UNDERLINED	ABBR	ABBREVIATIONS:					
1		1	5.4				Ford E-250	) Natur	Natural Gas						
1		2	5.4			Ford F-150 Natural Gas									
*		•	*			•									
*		*	*			•									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.) Since no NMOG RAF is adopted by the ARB for medium-duty SULEVs, the manufacturer has agreed to a default value listed below.

	OG FLE RAGE [g		NMOG @ CH4 RAF		NMOG or													
CER	ERT STD		NMOG	NMHC	NMHC	diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram mg=milligram mi=mile K=1000 miles F=degrees Fahrenheit SFTP=supplemental federal test procedure												
*		• 7	CERT [g/mi]	CERT [g/mi]	[g/mi]		[g/mi]		Ox [g/mi]			[mg/mi]	PM [		Hwy NO			
						CERT	STD	CER	T STI	D	CERT	STD	CERT	STD	CERT	STD		
	@		0.015	*	0.059	0.8	0.8 2.5		0.3	0.3 1		6	*	*	0.1	0.6		
		@ UL	0.022	*	0.084	0.8	3.7	0.23	0.4	5	1	8	*	*	0.21	0.90		
7.7.	@ 50°F	& 4K	*	*	*	*	*	*	•		*	*	*	*	*	*		
CO [ @ 20	°F&	L	= @ 4K (SUL EV) or 50K (T	ier 1, TLEV	NMHC+NO (comp		CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]			CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50	K	SFTP 2 = @ UL (Tier 1, TLEV)			CERT	STD	CERT	STD	CERT	ST	D CE	RT ST	CER	T STD	CERT	STD		
CERT	*		1 Jan 19 5	SFTP 1	*	*	*	*	*	*		* *	*	*	*	•		
STD	*		2.0	SFTP 2	*	*	•	*	*	*		•	*	*	*	*		
@ UL	EV	APOR/	ATIVE FAN	IILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				E	EVAPORATIVE FAMILY 4				
<u></u>	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RI	ORV	R 3-D	2-D	RL	ORVR		
CERT	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*		
STD	*	*	•	*	*	*	*	*	*	*	*	*	*	*	*	*		

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-010-1053 dated July 10, 2001.

Executed at El Monte, California on this \_\_\_\_\_\_ day of February 2002.

Allen Lyons, Chief

New Vehicle/Engine Programs Branch