

DAIMLERCHRYSLER CORPORATION

EXECUTIVE ORDER A-009-0568
New Passenger Cars, Light-Duty Trucks
and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEAR			T GROUF	^	VEHICLE TYPE C=passenger car; LDT=light-duty tru- IDV=medium-duty vehicle; LVW=load vehicle weight; ALVW=adjusted LVW	ed vehicle:	ssion V:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200			(T03.75B)		MDV: 3751-5750 pounds ALVW		TIER 1		120K / 120K	Gasoline (Indolene)			
No.	FAM	VAPORATIVE AMILY (EVAF)		No.	SPECIAL FEATUR EMISSION CONTROL SYS	ES & STEMS (ECS)	* = not applicable	OC	OC/TWC=oxidizing/3-way cat ADSTWC-adopting 7				
1	2CR)	CRXE0174GDL			HO2S(2), T	WC, SFI, OBD (F		J= Warm•UD Cat. U25/F	D2S=0YVgen concor/books 4 Occ				
2	2CR)	CRXE0174GEL				*	ga	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed					
3		*				*		TB	TBI= throttle body injection TC/SC=turbo /super charges				
4		*		4		*	CA	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parailel (2) suffix=series					
EVA		CS	ENGINE		VEHICLE	VEHICLES SUB.	IECT TO SETD	<u> </u>	4				
No.	1	No.	SIZE (L)		MAKES & MODELS STANDARDS ARE UNDERLINED				ABBREVIATIONS:				
1		1	3.7				Dodge Ram 1500 Pickup						
2		1	3.7				Dodge Ram 1500 Pickup						
*		•	*				ouge Nam 1500 Pic	жир					
* * *			*										

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NM AVE	NMOG FLEET NMOG @ RA AVERAGE [g/mi] CH4 RAF =				NMOG or												
	CER	T	STD	NMOG CERT	NMHC	NMHC STD	mg=millig	ıram mi	- [B] . u.	nning loss 1000 miles	OWALL	gryanon	uispenseo!	=on-poard i	efueling vap piemental fe	OF FECOVER	a=aram	
*		*		[g/mi]	CERT [g/mi]	[g/mi]		[g/mi]		Ox [g/mi]	H	1CHO[1	[mg/mi]	PM [[g/mi]	Hwy NO		
		10.40		(3)		 	CERT	STD	CERT	r st	D C	ERT	STD	CERT	STD	CERT	STD	
1	12		@ 50K		0.15	0.32	2.0	4.4	0.5	0.	7	•	•	*	*	0.3	1.4	
-		4.4	@ UL		0.15	0.46	2.0	6.4	0.47	0.9	8	*	*	*	*	0.26	1.96	
Ĺ		@ 50°	F & 4K		*	*			*	*		*	*	*	*	*	*	
	@ 20	O°F & 📳 LE		1 = @ 4K (SULEV, ULEV, .EV) or 50K (Tier 1, TLEV) 2 = @ UL (Tier 1, TLEV)				e) (composite)		NMHC+NOx [g/mi] [US06]					HC+NOx		[g/mi] 2031	
-		-	GFIF Z -	· @ UL (1 ler		CERT	STD	CERT	STD	CERT	STD	CEF	T STD			CERT	STD	
L	CERT	10.2			SFTP 1	*	*	•	*	*				•		*	*	
	STD	12.5	100	V 1	SFTP 2	*	*	*	*	*	*	*	+	+	-	*	•	
- 1	@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3) F	EVAPORATIVE FAMILY 4			
		3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR		2-D	RL	ORVR	
-	CERT	1.1	0.7	0.001	*	1.1	0.7	0.001	*	*	•	*	*	*	+ 2-0	KL	URVR *	
Ŀ	STD	2.0	2.5	0.05	*	2.5	3.0	0.05	*	*	*	*	+	-	+	-	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 2871 day of February 2002.

Allen Lyons, Chief

New Vehicle/Engine Programs Branch