

FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1011 w Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

2		1 2.0			Ford Focus; Ford Focus Wagon OBD (P)								
1	2 2.0			Ford Escort ZX2 OBD (F)									
1	1 1		2.0		Ford Escort OBD (F)								
EVAF No.		ECS ENGIN					ECT TO SFTP E UNDERLINED	ABBREVIATIONS:					
4		* 989.1.560.79		4	# CO = 10 Main 1975 Carried 1975		OBD (F) / OBD (P) = on-board diagnosis; full / partial compliance (prefix) 2 = parallel (2) (suffix) = serie						
3		*		3	*		MFI = multiport fuel injection SFI = sequential MF TC/SC = turbo/super charger CAC = charge air coole						
2	2FM	2FMXR0080BBE			TWC, HO2S(2),	SFI, OBD (F	HO2S = heated O2S EGR = exhaust gas recirculation AIR = secondary air injection PAIR = pulsed AIR						
1	2FM	XR008	OBAE	1	TWC, HO2S(2), EG	R, SFI , OBD	(F, P)	catalytic converter O2S = ovugen sensor					
No.		EVAPORATIVE AMILY (EVAP)			SPECIAL FEATURES (EMISSION CONTROL SYSTEM		* = not applicabl	TWC = 3-way catalytic converter WUTWC = warm-up TWC ADSTWC = adsorber TWC OC = oxidation					
2002		2FMXV02.0VF3			Passenger Car	Low E	mission Vehicle (LEV)	Gasoline (Indolene)					
MODEL YEAR 1		TES	TEST GROUP		VEHICLE TYPE		UST EMISSION ARD CATEGORY	FUEL TYPE					

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

NMOG FLEET AVERAGE [g/mi] NMOG @RAF			= 1.00	CH4 = methane NMOG = non-CH4 organic gas NMHC = non-CH4 hydrocarbon CO = carbon monoxide NOx = oxides of nitrogen HCHO = formaldehyde PM = particulate matter RAF = reactivity adjustment factor													
CERT STD		CH4 RAF = *		CO [g/mi]			NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]			Hwy NOx [g/mi]			
0.068	0.06	68 (ERT	STD	CERT STD		CI	ERT	STD	CERT	STD	CER	T S	TD	CERT	STD
	@			.047	0.075	0.4	3.4 4.2	0.1	0.1	0.2	1	15 18	*		•	0.05	0.3
K ≃ 1000 miles	@ 1			.053	0.090	0.5			0.1				*	*	•	0.1	
	@ 50°f			•					•				*		•	*	
	[g/mi] 0°F, 50K			g = gram mg = milligram		NMHC+i (com	NN	NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		g/mi]	CO [g/mi] [SC03]		
CERT	STD		mi = m			CERT	STD	CI	ERT	STD	CERT	STD	CER		TD	CERT	STD
2.1	10.	10.0		@ 4K		*	*	0.07		0.14	7.0	8.0	0.01		0.2	0.4	2.7
F = degree	Fahrenh	Fahrenheit		@ 100K		*	*	*		*	*	•	*	*		*	•
@ 100K	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2				EV	VAPORATIVE FAMILY 3			EVAPORATIVE FAMILY 4			LY 4	
100K	3-D	2-D	•	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	0.7	0.6		0.01	0.13	0.7	0.6	0.01	0.13	*	*	*	*		*	*	*
STD	2.0	2.5		0.05	0.20	2.0	2.5	0.05	0.20	*		*	*	*		*	•
2-D, 3-D [g	/test] = 2-d	lay, 3-c	day c	diurnal a	nd hot-soak		RL [g/mi] =	runnir	g loss		ORVR [g/ga	ilon of fue	l dispense	d] ≃ on-b	oard ref	ueling vapor	recovery

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of June 2001

R. B. Summerfield, Chief

Mobile Source Operations Division