## FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1016 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR TEST			T GROU	Р	VEHICLE TYPE		AUST EMISSION DARD CATEGORY	FUEL TYPE					
200	2	2FMXV02.5VD5			Passenger Car	Transiti	onal Low Emission Vehicle (TLEV)	Gasoline (Indolene)					
No.		APORA MILY (E		No.	SPECIAL FEATURES EMISSION CONTROL SYST		* = not applicable	TWC = 3-way catalytic converter WUTWC = warm-up TWC ADSTWC = adsorber TWC OC = oxidation					
1	2FM	XR011	5BBE	1	2TWC, TWC, 2H02S	(2), EGR, SFI,	catalytic converter O2S = oxygen sensor						
2		*		2		*	HO2S = heated O2S EGR = exhaust gas recirculation AIR = secondary air injection PAIR = pulsed AIR						
3		*		3		*	MFI = multiport fuel injection SFI = sequential MFI TC/SC = turbo/super charger CAC = charge air cooler						
4		*		4		*	OBD (F) / OBD (P) = on-board diagnosis; full / partial compliance (prefix) 2 = parallel (2) (suffix) = serie						
EVAI No.	P ECS ENGINE No. SIZE (L)			VEHICLE VE	HICLES SUB.	JECT TO SFTP RE UNDERLINED							
1	1		2.5		Mercury Cougar								
*	* *		*		*								
*		* *			*								
*	* *		* *				*						

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

NMOG FLEET AVERAGE [g/mi]			NMOG [g/mi] @RAF = 1.00		CH4 = methane NMOG = non-CH4 organic gas NMHC = non-CH4 hydrocarbon CO = carbon monoxide NOx = oxides of nitrogen HCHO = formaldehyde PM = particulate matter RAF = reactivity adjustment factor											
CERT	CERT STD		CH4 RAF = *		CO [g/mi]			NOx [g/mi]		HCHO [mg/mi]			PM [g/mi]		Hwy NOx [g/mi]	
0.068	0.068		CERT	STD	CERT	STD	С	ERT	STD	CERT	STD	CER		TD	CERT	STD
	@ 50	K	0.074	0.125	0.4	3.4		0.1	0.4	1	15			*	0.1	0.5
K = 1000 miles	@ 100	ĸ	0.084 0.156		0.6	4.2		0.1	0.6	1	18	*	*	*	0.1	0.8
	@ 50°F, 4	K	*	*	*	*		*	*	*	*	•		*	*	*
CO [g/mi] @ 20°F, 50K			g = gr mg = i	am milligram	NMHC+NOx [g/mi] (composite)			NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMH	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
CERT	STD		mi = mile		CERT	T STD		CERT ST		CERT	STD	CER	CERT S		CERT	STD
2.5	5 10.0			@ 4K		*		*	*	*	*	*		•	*	*
F = degree Fahrenheit			@ 100K		*	*		*	*	*			*		*	
@ T	EVAPORATIVE FAMILY 1			EVAPORATIVE FAMILY 2 E				EV	APORATI	LY3	EVAPORATIVE FAMILY 4					
100K	3-D	2 <b>-</b> D	RL	ORVR	3-D	2-D	RL	ORVR		2-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	1.5	1.3	0.01	0.12	*	*	*	*	*	•	*	*	*	*	*	*
STD	2.0	2.5	0.05	0.20	*	* * ,		*	*	*	*		*	-	*	*
2-D, 3-D [g/t	est] = 2-day,	3-day	y diurnal a	nd hot-soak		RL [g/mi]	= runnii	ng loss		ORVR [g/ga	llon of fue	l dispense	d] = on b		.alina wasa	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of August 2001.

R. B. Summerfield, Chief Mobile Source Operations Division