



## TOYOTA MOTOR CORPORATION

EXECUTIVE ORDER A-014-0410 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26 Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE		TEST GROUP		VEHICLE TYPE	EXHAUST EMISSIO CATEGO		FUEL TYPE				
2002	2TYX	2TYXV01,5LJ1		Passenger Car	"LEV II" Super Ultra Low (LEV II SU		Gasoline plus Battery-Assist				
No.	EVAPORATIV FAMILY (EVAI		No.	SPECIAL FEATURES EMISSION CONTROL SYSTI WUTWC, ADSTWC, HO	EMS (ECS) applicable	TWC = 3-way cata ADSTWC = adsort HO2S = heated 02 HAFS = heated/AF	per TWC O2S = oxygen sensor 2S AFS = air / fuel sensor (aka. universal O2S)				
2	+		2	*		MFI = multiport fuel injection SFI = sequential MFI OBD (F) / OBD (P) = on-board diagnostics; full / partial compliance (prefix) 2 = parallel (2) (suffix) = series					
3	* .		. 3	*							
EVAF No.	P ECS			VEHICLE MAKES & MODELS							
1	1	1 1.5		Toyota: Prids							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

NMOG FLEET NMOG [g/mi] AVERAGE [g/mi] @ RAF = 1.00					CH4 = methane NMOG = non-CH4 organic gases NMHC = non-CH4 hydrocarbons CO = carbon monoxide NOx = oxides of nitrogen HCHO = formaldehyde PM = particulate matter RAF = reactivity adjustment factor										
CERT STD		7	CH4 RAF = *		CO [g/mi]		NOx [g/phi]		HCHO [mg/mi]		PM [g/ml]			Hwy NOx [g/mi]	
0.061	0.068	0.068 CEF		ERT STD		STD	CERT	STD	CERT	STD	CERT	STE	ם כ	CERT	STD
	@ 50K		•	*	*	*	1.7	*	*	*	•	•		•	
K = 1000	@ 120K		0.003		0.4	1.0	0.01	0.02 1 0.02	0.02	4 8	•	*		0.01	0.03
miles	@ 50°F, 4K	_	.011												
CO [g/mi]			NMHC+NOx [g/mi] NMHC+NOx [g/mi] (composite) [US06]			CO [g/mi] NMH0 [US06]			C+NOx [g/mi] [SC03]		CO [g/mi] [SC03]				
CERT	STD	٦.	mg = milligram mi = mile @ 4K		CERT	STD	CERT	STD	CERT	STD	CERT	r STI	D	CERT	STD
1.8	10.0	1			•	1	0.01	0.14	0.1	8.0	0.02	0.20	0	0.5	2.7
F = degree Fahrenhelt		1		@ 120K	*	7.	*	*	*	*	•	*			*
	EVAPORATIVE FAMILY 1			EVAPORATIVE FAMILY 2 EV				VAPORATIVE FAMILY 3			EVAPORATIVE FAMILY 4				
@ 120K	<del></del>	-D	RL	ORVR	3-D	2-D	RL OR	VR 3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT		.4	0.01	0.01	1 1/1	*	•		•	*	•	*	*	•	•
STD	2.0	.5	0.05	0.20	<del>                                     </del>	4	*		•	*	•	•	*	•	*
	test] = 2-day,	3-dav	diumal a	and hot-soal	k /	RL [g/mi] =	running los	is.	ORVR [g/g	allon of fue	i dispense	d] = on-boa	ard refu	ieling vapoi	recovery

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaustements on Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

BE IT FURTHER RESOLVED: That the listed vehicle models are conditionally certified pursuant to 13 CCR Section 1968.1(m)(6.2) ("Malfunction and Diagnostic System Requirements—1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines") because the on-board diagnostic II system of the listed vehicle models has been determined to have four deficiencies. The listed vehicle models are approved subject to Toyota Motor Corporation paying a fine of seventy-five dollars (\$75.00) per vehicle for the third and fourth deficiencies in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the vehicle manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California under this conditional certification, and pay the full fine owed for that quarter pursuant to this conditional certification; payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty days after the end of each calendar quarter during the 2002 model year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$5,000 per vehicle pursuant to Health and Safety Code Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

R. B. Summerfield, Chief Mobile Source Operations Division