

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	FUEL TYPE
2002	2TYXV03.0JJA	Passenger Car	Ultra Low Emission Vehicle (ULEV)	Gasoline

No.	EVAPORATIVE FAMILY (EVAP)	No.	SPECIAL FEATURES & EMISSION CONTROL SYSTEMS (ECS)	* = not applicable	TWC = 3-way catalytic converter ADSTWC = adsorber TWC HO2S = heated O2S AFS = air / fuel sensor (aka. universal O2S) HAFS = heated AFS AIR = secondary air injection MFI = multipoint fuel injection TC/SC = turbo/super charger OBD (F) / OBD (P) = on-board diagnostics; full / partial compliance (prefix) 2 = parallel	WUTWC = warm-up TWC O2S = oxygen sensor EGR = exhaust gas recirculation PAIR = pulsed AIR SFI = sequential MPI CAC = charge air cooler (2) (suffix) = series
1	2TYXR0135AK1	1	2WUTWC, TWC, 2HAFS, 2HO2S, EGR, SFI, OBD (P)			
2	*	2	2WUTWC, TWC, 2HAFS, 2HO2S, SFI, OBD (P)			
3	*	3	*			
4	*	4	*			

EVAP No.	ECS No.	ENGINE SIZE (L)	VEHICLE MAKES & MODELS	VEHICLES SUBJECT TO SFTP STANDARDS ARE UNDERLINED
1	1	3.0		<u>TOYOTA: CAMRY</u>
1	2	3.0		<u>LEXUS: ES 300</u>
*	*	*		*
*	*	*		*

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

NMOG FLEET AVERAGE [g/mi]		NMOG [g/mi] @ RAF = 0.94 CH4 RAF = *		CH4 = methane NOx = oxides of nitrogen		NMOG = non-CH4 organic gases HCHO = formaldehyde		NMHC = non-CH4 hydrocarbons PM = particulate matter		CO = carbon monoxide		RAF = reactivity adjustment factor	
CERT	STD	CERT	STD	CO [g/mi]		NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]	
0.061	0.068			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
K = 1000 miles	@ 50K	0.024	0.040	0.2	1.7	0.1	0.2	0.4	8	*	*	0.03	0.3
	@ 100K	0.034	0.055	0.3	2.1	0.1	0.3	0.5	11	*	*	0.05	0.4
	@ 50°F, 4K	0.075	0.080	0.3	1.7	0.1	0.2	1	16	*	*	*	*


CO [g/mi] @ 20°F, 50K		g = gram mg = milligram mi = mile	NMHC+NOx [g/mi] (composite)		NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
CERT	STD		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
4.9	10.0											
F = degree Fahrenheit		@ 4K	*	*	*	*	*	*	*	*	*	*
		@ 100K	*	*	*	*	*	*	*	*	*	*

@ 100K	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	0.4	0.8	0.01	0.01	*	*	*	*	*	*	*	*	*	*	*	*
STD	2.0	2.5	0.05	0.20	*	*	*	*	*	*	*	*	*	*	*	*

2-D, 3-D [g/test] = 2-day, 3-day diurnal and hot-soak RL [g/mi] = running loss ORVR [g/gallon of fuel dispensed] = on-board refueling vapor recovery

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 31st day of July 2001. 
R. B. Summerfield, Chief
Mobile Source Operations Division