

TOYOTA MOTOR CORPORATION

EXECUTIVE ORDER A-014-0423-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE		GROUP		VEHICLE TYPE		AUST EMISSION PARD CATEGORY	FUEL TYPE Gasoline						
2002	2TYX	(V04.3JJB		Passenger Car	Ultra Lov	w Emission Vehicle (ULEV)							
No.	EVAPORA FAMILY (No.	SPECIAL FEATURE EMISSION CONTROL S		* = not applicable	TWC = 3-way catalytic converter WUTWC = warm-up TWC ADSTWC = adsorber TWC OC = oxidation						
1	2TYXR01	2TYXR0150AK1 2TYXR0160AK1		2TWC, TWC	, 2HO2S(2), SFI, OB	catalytic converter O2S = oxygen sensor HO2S = heated O2S EGR = exhaust gas recirculation							
2	2TYXR016				•	AIR = secondary air injection PAIR = pulsed AIF MFI = multiport fuel injection SFI = sequential MF TC/SC = turbo/super charger CAC = charge air coolei							
3	*			- ···	•								
4	*				•	OBD (F) / OBD (P) = on-board diagnostics; full / part compliance (prefix) 2 = parallel (2) (suffix) = ser							
EVAF No.	P ECS	ENGINE SIZE (L		VEHICLE MAKES & MODELS	VEHICLES SUB. STANDARDS AF								
1	1 4.3			Lexus: SC 430, GS 430									
2	1 4.3		1	Lexus: LS 430									
*	*			•									
*						•	· · · · · · · · · · · · · · · · · · ·						

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

NMOG FLEET AVERAGE [g/mi]		NMOG [g/mi] @ RAF = 0.94		CH4 = methane NMOG = non-CH4 organic gases NMHC = non-CH4 hydrocarbons CO = carbon monoxide NOx = oxides of nitrogen HCHO = formaldehyde PM = particulate matter RAF = reactivity adjustment factor												
CERT	CERT STD		CH4 RAF = *		CO [g/mi]		ì	NOx [g/mi]		HCHO [mg/mi]		Р	PM [g/mi]		Hwy NOx [g/mi]	
0.061	0.068		CERT	STD	CERT	STD	CI	ERT	STD	CERT	STD	CER	r s	TD	CERT	STD
K = 1000 miles	@ 5	ок	0.033	0.040	0.2	1.7	(0.1	0.2	0.2	8	*		•	0.03	0.3
	@ 10	@ 100K (0.037 0.055		2.1	(0.1	0.3	0.3	11	•		•	0.04	0.4
	@ 50°F,	4K	*	*	•	*		*	•	*	•	•		*	*	4
	[g/mi] °F, 50K		g = gram mg = milligram		NMHC+NOx [g/mi] (composite)] NN	NMHC+NOx [g/mi] [US08]		CO [g/mi] (US06)			NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
CERT	RT STD			ml = mile		STD	CI	ERT	STD	CERT	STD	CER	r s	TD	CERT	STD
2.5	2.5 10.0			@ 4K		•		*	•		•	•		•	•	*
F = degree	Fahrenheit	it		@ 100K	٠			*	*	*	•	•		•	•	•
@	EVAPORATIVE FAMILY 1			EVAPORATIVE FAMILY 2			EVAPORATIVE FAMILY 3			_Y 3	EVAPORATIVE FAMILY 4					
100K	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	0.4	0.5	0.01	0.01	0.5	0.6	0.01	0.05	•	+	•	•	•	•	•	*
STD	2.0	2.5	0.05	0.20	2.0	2.5	0.05	.05 0.20		+	*	•		*	*	•
2-D, 3-D [g/	test] = 2-da	y, 3-da	ay diumal a	and hot-soal	<u> </u>	RL [g/mi]	= runni	ng loss	-	ORVR [g/ga	illon of fue	l dispense	d] = on-be	oard refu	ieling vapo	r recovery

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-14-423 dated February 26, 2001.

Executed at El Monte, California on this 3 20 day of August 2001.

R. B. Summerfield, Chief Mobile Source Operations Division