

## NISSAN MOTOR CO., LTD

EXECUTIVE ORDER A-015-0371-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD		TEST GROUP			VEHICLE TYPE  PC=passenger car; LDT=light-duty true  IDV=medium-duty vehicle; LVW=loade  vehicle weight; ALVW=adjusted LVW;	k; CATEGOR'	EMISSION STANDAI Y (LEV=low emiss LEV= transitional LEV; LEV; SULEV=super ULE	ION EVAPORATIVE USEFUL LIFE	FUEL TYPE (CNG/LNG=compressed/ iliquefied natural gas; LPG=liquefied petroleum gas)				
2002 2NSXT0			T02.4C4	A	LDT: 3751-5750 pounds LVW		LEV	100K / 100K	Gasoline				
No.		PORATIVE (EVAF)				No.	SPECIAL FEATURI EMISSION CONTROL SYS		* = not applicable	OC/TWC=oxidizing/3-way	cat. ADSTWC=adsorbing TWC		
1	2NSXR	SXR0110RCC			TWC(2), HO2S(	2), EGR, SFI, OBI	AFS/HAFS=air-fuel ratio :	sensor/heated AFS EGR=exhaust					
2		•				* -	AIR MFI/SFI= multipor	IR≃secondary air injection/pulsed rt fuel injection/sequential MFI					
3		•				*	TBI= throttle body injection	on TC/SC=turbo /super charger DBD (F) / (P)=full /partial on-board					
4						*		diagnostic prefix 2=para	illel (2) suffix=series				
EVA. No.	F EC		ENGINI SIZE (L			VEHICLES SUBJ STANDARDS AR		ABBREVIATIONS: *					
1	1	1 2.4			NISSAN XTERRA 2WD WAGON XE								
*	*	* *			·								
*	* *												
*	*		*										

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF=0. AVERAGE [g/mi] CH4 RAF = *				CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon C NMOG or introgen HCHO=formaldehyde PM=particulate matter RAF=reactivity adju NMHC diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-bo							itv adiustm/	ent factor	2/3 D [g/test	]=2/3 dav	
CER'	111114		NMOG NMHC	NMHC STD	mg=millig	ram mi=	∟igumu,=rui mile K=1	1000 miles	F=de	ig/gallor grees F	i dispensedj ahrenheit	≃on-ocard SFTP=sup	retuesing vap plemental fe	ior recovery derai test pi	g≖gram rocedure
0.100	0.095	CERT   CERT   [g/mi]		[g/mi]		(g/mi)		x [g/ml]			mg/ml]		g/mi]	Hwy NO	
		[g/mi]	fāvimi		CERT	STD	CERT	ST	D C	ERT	STD	CERT	STD	CERT	STD
	@ 50K	0.031	*	0.100	1.2	4.4	0.03	0.	4	0.4	18	*	*	0.01	0.5
	@ UL	0.033	•	0.130	1.3	5.5	0.04	0.	5	0.5	23	*	*	0.02	0.7
	@ 50°F & 4K	0.086		0.200	2.2	4.4	0.04	0.	4	1	36	*	*	•	*
CO [9	F& L	= @ 4K (SUL EV) or 50K (TI	er 1, TLEV)	NMHC∓No (comp		CO [	g/mi] oosite)		C+NOx   [US06]	-	CO [g/mi] [U\$06]		HC+NOx ni] [SC03]		[g/mi] 003]
50	K SFTP 2	≖ @ UL (Tier	1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CE	RT ST	) CER	T STD	CERT	STD
CERT	5.3	/* <b>(a</b>	SFTP 1	•		*	*	*	*	Π.	*	ń	+	•	•
STD	12.5		SFTP 2	*		*	*	*	*	,		*	*		•
@ UL	EVAPOR	EVAPORATIVE FAMILY 2 EVAPOR.				PORAT	RATIVE FAMILY 3			EVAPORATIVE FAMILY 4					
	3-D 2-l	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV	R 3-D	2-D	RL	ORVR
CERT	0.6 0.9	5 0.00	0.03		*	*	*	*	*	*	•	*	*	*	*
STD	2.0 2.1	5 0.05	0.20	•	*	*	*	*	•	*	*	*		*	•

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes and replaces Executive Order A-015-0371 dated July 10, 2001.

Executed at El Monte, California on this \_\_\_\_\_\_ day of May 2003.

Allen Lyons, Chief

Mobile Source Operations Division