

MITSUBISHI MOTORS CORPORATION

EXECUTIVE ORDER A-086-0256 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL TEST GROUP			JP		VEHICLE TYPE		AUST EMISSION DARD CATEGORY	FUEL TYPE						
200	2	2MTXT03.5GNS				3751-5750 Pounds Loaded Vehicle Weight Light-Duty Truck	Low	Emission Vehicle (LEV)	Gasoline					
No.		VAPORATIVE AMILY (EVAP)		I	No.	SPECIAL FEATUR		TWC = 3-way catalytic converter WUTWC = warm-up TWC ADSTWC = adsorber TWC OC = oxidation						
1	2MTX	(R017	R0175A1A			2WUTWC, TWC, 2	HO2S(2), SFI, EGI	catalytic converter O2S = oxygen sensor HO2S = heated O2S EGR = exhaust gas recirculation						
2	2MTXR0200A1A				2		•	AIR = secondary air injection PAIR = pulsed AIR						
3		*	* 3				•	MFI = multiport fuel injection SFI = sequential MF TC/SC = turbo/super charger CAC = charge air coole						
4					4		*	OBD (F) / OBD (P) = on-board diagnosis; full / partial compliance (prefix) 2 = parallel (2) (suffix) = serie						
EVAF No.	P ECS ENGINE No. SIZE (L)			VEHICLE VEHICLES SUBJECT TO SFTP MAKES & MODELS STANDARDS ARE UNDERLINED										
1	1 1 3.0			MITSUBISHI MONTERO SPORT										
1	1 3.5			MITSUBISHI MONTERO SPORT										
2	٠,	1	3.5		Ī	MITSUBISHI MONTERO								
*						•								

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

	FLEET GE [g/mi]			NMOG @RAF	= 0.94	CH4 = n NOx	nethane = oxides			H4 organic CHO = form	aldehyde		CH4 hydrodiculate ma			arbon mor ctivity adju		
CERT STD				CH4 R	AF = *	CO [g/mi]			NOx [g/ml]		HCHO [mg/mi]		PM [g/mi]		.	Hwy NOx [g/mi]		
0.100 0.095		5	CERT		STD	CERT	STE) C	ERT	STD	CERT	\$TD	CER	T S	TD	CERT	STD	
K = 1000 miles	@ :	@ 50K		.052	0.100	0.8 4.4			0.1	0.4	1	18	•		*	0.03	0.5	
	@ 10	@ 100K		.057	0.130	1.0	5,5		0.2	0.5	1	23	•		*	0.03	0.7	
	@ 50°F,	4K	0	.120	0.200	1.8	4.4	0.	0.03	0.4	1	36	•		•	•	•	
	[g/mi] F, 50K			g = gram mg = milligram		NMHC+NOx [g/mi] (composite)		ıi] Ni	NMHC+NOx [g/mi] [US06]		CO [g/mi] {U\$08}			NMHC+NOx [g/mi] (SC03]		CO [g/ml] [SC03]		
CERT	STD]		mi=n		CERT	STD) С	ERT	STD	CERT	STD	CERT	r s	TD	CERT	STD	
8.3	12.5			@ 4K @ 120K		•	•	-	1.07	0.25	4,6	10.5	0.06	0.27	.27	0.6	3.5	
F = degree	Fahrenheit					4	•		•						•			
æ	EVAF	TIVE FAMILY 1			EVAPORATIVE F			FAMILY 2 EV		APORATIVE FAMILY		LY 3	EVAPOR		ATIVE FAMILY 4			
@ 100K	3-D	2-D		RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	
CERT	1.1	2.0		0.03	0.01	1.0	0,9	0.04	0.07	1	•	•	•	*	•	*	•	
STD	2.0	2.0 2.5		0.05	0.20 2.0 2.5 0.05		0.20	•			•	•	٠	•	•			
2-D, 3-D [g/t	test] = 2-da	y, 3-da	ay d	liurnal ac	nd hot-soak	recovery	R	L (g/mi) =	running	loss	ORVR [g/ga	allon of fue	i dispense	d] = on-b	pard refu	eling vapor	recovery	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______day of July 2001

R. B. Summerfield, Chief Mobile Source Operations Division