

MAZDA MOTOR CORPORATION

EXECUTIVE ORDER A-016-0262 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| MODE | | TEST GROUP | | VEHICLE TYPE | EXHAUST EMISSION STANDARD CATEGORY | FUEL TYPE Gasoline | | | | | |
|------|--------------------|-----------------|-----|--|--|--|--|--|--|--|--|
| 2002 | 2TKX | 2TKXV02.5BMA | | Passenger Car | Transitional Low Emission Vehicle (TLEV | | | | | | |
| No. | EVAPOR FAMILY (| | No. | SPECIAL FEATURES & EMISSION CONTROL SYSTEM | | [] IVC ADSITIC - ausoider IVC OC - Oxidation | | | | | |
| 1 | 2TKXR01 | 5PMC | 1 | 2WUTWC, TWC, 2HO2S(| 2), SFI, EGR, OBD(F) | catalytic converter O2S = oxygen senso HO2S = heated O2S = EGR = exhaust gas recirculatio | | | | | |
| 2 | • | | 2 | • | | AIR = secondary air Injection PAIR = pulsed AIF MFI = multiport fuel injection SFI = sequential MFI TC/SC = turbo/super charger CAC = charge air coole | | | | | |
| 3 | * | | 3 | * | Wath | | | | | | |
| 4 | * | • | | • | | OBD (F) / OBD (P) = on-board diagnosis; full / partial compliance (prefix) 2 = paratiel (2) (suffix) = serie | | | | | |
| EVAF | ECS No. | ENGIN SIZE (| | | CLES SUBJECT TO SFTP DARDS ARE UNDERLINED | | | | | | |
| 1 | 1 | 2.5 | | Mazda 626 | | | | | | | |
| • | • | * * | | * | | | | | | | |
| * | • | | | * | | | | | | | |
| • | -+- | • | | | • | | | | | | |

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

| | FLEET | 1 | | NMOG @ RAF | [g/mi] = 0.98 | CH4 = m NOx = ox | ethane N ides of nitr | MOG = no ogen l | | organic g formald | | | CH4 hydro ate matter | | | = carbon mo ity adjustm | |
|--------------------------|-------------|--------------------|-------------|---------------|------------------|--------------------------------|--------------------------|--------------------|---------------------------|----------------------|---------------------|--------------|-------------------------|---------------------------|----------------|----------------------------|------------|
| CERT | STE |) | CH4 RAF = * | | | co | NOx [g/ml] | | HCHO [mg/mi] | | P | PM [g/mi] | | | Hwy NOx [g/mi] | | |
| 0.063 | 0.06 | 8 | CERT | | STD | CERT | STD | CER | ī | \$TD | CERT | STD | CERT | r s | TD | CERT | STD |
| | œ. | 50K | 0. | .080 | 0.125 | 0.9 | 3.4 | 0.2 | | 0.4 | 1 | 15 | • | | • | 0.1 | 0,5 |
| K = 1000 miles | @ 1 | 00K | 0.096 | | 0.156 | 1.1 | 4.2 | 0.2 | | 0.6 | 1 | 18 | * | | * | 0.1 | 0.8 |
| mues | @ 50°F | , 4K | | * * | | * | | | | | | | | | * | * | |
| CO [g/mi] @ 20°F, 50K | | | | g = gr | am milligram | NMHC+NOx [g/mi] (composite) | | NMH | NMHC+NOx [g/mi] [US06] | | CO [g/mi] [US06] | | | NMHC+NOx [g/mi] {SC03] | | CO [g/mi] [SC03] | |
| CERT | STD | | mi≖mi | | | CERT | STD | CER | T | STD | CERT | STD | CERT | r s | TD | CERT | STD |
| 5.1 | 10.0 |) | | | @ 4K | • | * | • | | * | • | • | | • | * | • | |
| F = degree | Fahrenhe | it | | @ 100K | | * | * | • | | * | • | * | • | | • | * | * |
| @ | EVA | APORATIVE FAMILY 1 | | | | EVAPORATIVE FAMILY 2 | | | E | EVAPORATIVE FAMILY 3 | | | EVAPORATIVE FAMILY 4 | | | | |
| 100K | 3-D | 2-0 | 5 | RL | ORVR | 3-D | 2-D | RL | ORVR | 3-D | 2-D | RL | ORVR | 3-D | 2-D | RL | ORVR |
| CERT | 0.8 | 0.8 | 3 | 0.003 | 0.05 | ٠ | • | * | * | • | • | • | • | * | • | • | • |
| STD | 2.0 2.5 | | 5 | 0.05 | 0.20 | • | * | • | • | • | * | • | * | • | • | • | • |
| 2-D, 3-D [g/ | test] = 2-d | ay, 3- | day d | liurnal a | nd hot-soak | | RL [g/mi] | = running | loss | · | ORVR [g/g | allon of fue | dispense | d] = on-b | oard re | lueling vapo | r recovery |

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of July 2001

R. B. Summerfield, Chief Mobile Source Operations Division