

## MAZDA MOTOR CORPORATION

**EXECUTIVE ORDER A-016-0264** New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9:

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE YEAR		r GROU	>	VEHICLE TYPE		AUST EMISSION DARD CATEGORY	FUEL TYPE  Gasoline						
2002	2ТКХ	V02.5BM	В	Passenger Car		Transitional ssion Vehicle (TLEV)							
No.	EVAPOR FAMILY (		No.	SPECIAL FEATURES EMISSION CONTROL SYSTI		* = not applicable	TWC = 3-way catalytic converter WUTWC = warm-up TWC ADSTWC = adsorber TWC OC = oxidation						
1	2TKXR01	50PPA	1	2WUTWC, TWC, 2HO	2S(2), SFI, EGI	catalytic converter O2S = oxygen sensor HO2S = heated O2S							
2	*	•			4	AIR = secondary air injection PAIR = pulsed AIR							
3	*	*		1	*		MFI = multiport fuel injection SFI = sequential MFI TC/SC = turbo/super charger CAC = charge air cooler						
4	*				•	OBD (F) / OBD (P) = on-board diagnosis; full / partial compliance (prefix) 2 = parallel (2) (suffix) = serie							
EVÁF No.	ECS No.	ENGIN SIZE (				JECT TO SFTP RE UNDERLINED							
1	1 1 2.5			Mazda Millenia									
*	•	• •			•								
*	+	•				•							
•	*	* *		*									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

NMOG FLEET AVERAGE [g/mi]			NMOG @ RAF	[g/mi] = 0.98	CH4 = methane NMOG = non-CH4 organic gases NMHC = non-CH4 hydrocarbons CO = carbon monoxide NOx = oxides of nitrogen HCHO = formaldehyde PM = particulate matter RAF = reactivity adjustment factor												
CERT	CERT STD		CH4 RAF = *		CO [g/mi]			NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]			Hwy NOx [g/mi]		
0.063	0.06	38	CERT STD		CERT	STD	CE	RT	STD	CERT	STD	CERT	S	TD	CERT	STD	
	Ø.	50K	0	.093 0.125		0.9	3.4	0	),1	0.4	1	15	*		•	0.1	0.5
K = 1000 miles	@	100K		0.098 0.15		1.0	4.2	0	).1	0.6	1	18	*		•	0.1	0.8
	@ 50°l	F, 4K		•	•	•	*		*	*	•	•	•		•	•	*
	[g/mi] °F, 50K			g = gram mg = milligram		NMHC+NOx [g/mi] (composite)		] NM	NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		/mi]	CO [g/mi] [SC03]	
CERT			1	mi ≄ mile		CERT	STD	CE	CERT S		CERT	RT STD	CERT	S	TD	CERT	STD
5.5	10.0			@ 4K		*	•	•		•		*	•			*	*
F = degree	Fahrenh	hrenheit		@ 100K			*	* *		•	*	• •				•	•
<u></u>	EVAPORATIVE FAMILY 1				ILY 1	EVAPORATIVE FAMILY 2				ΕV	EVAPORATIVE FAMILY 3			EVAPORATIVE FAMILY 4			
@ 100K	3-D	2-0	)	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	1.0	1.1	1	0.005	0.03	*	٠	*	•	•	•	•	•	*	•	•	•
STD	2.0	2.0 2.5		0.05	0.20	0.20 * * * *		*	•	*	*	*	*	•	-	*	
2-D, 3-D [g/	test] = 2-c	lay, 3-	day c	diurnal a	nd hot-soak		RL [g/mi]	= runnin	ng loss		ORVR [g/g:	alion of fuel	dispense	i] = on-bo	oard ref	ueling vapo	r recovery

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_\_\_ day of July 2001

R. B. Summerfield, Chief Mobile Source Operations Division