## HONDA MOTOR CO., LTD.

EXECUTIVE ORDER A-023-0321 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

TIS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE		TEST GROUP		VEHICLE TYPE		AUST EMISSION DARD CATEGORY	FUEL TYPE					
2002	2 2HNX	V01.74W	N	Passenger Car	En	l" Super Ultra Low nission Vehicle LEV II SULEV)	Compressed Natural Gas					
No.		EVAPORATIVE AMILY (EVAP) HNXR0000AAJ		SPECIAL FEA EMISSION CONTROL	TURES & SYSTEMS (ECS)	* = not applicable	TWC = 3-way catalytic converter WUTWC = warm-up TWC OC = oxidation catalytic converter O2S =					
1	2HNXR000			TWC, HO2S	(2), SFI, WUTWC, O	oxygen sensor AFS/HAFS = air/fuel sensor (aka. Universal O2S)/ heated AFS						
2	*	*			*	HO2S = heated O2S EGR = exhaust gas recirculation						
3	*		3		*	AIR = secondary air injection PAIR = pulsed AIF  MFI = multiport fuel injection SFI = sequential ME						
4	*		4		*	TC/SC = turbo/super charger CAC = charge air coole OBD (F) / OBD (P) = on-board diagnosis; full / partial compliance (prefix) 2 = parallel (2) (suffix) = serie						
EVAF No.	ECS No.	ENGIN SIZE (I		VEHICLE MAKES & MODELS		JECT TO SFTP	ABBREVIATIONS:					
1	1	1.7				Honda Civic GX						
*	*	•										
*	*	* *										
*	*	*			1-11-1							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing. Since no NMOG RAF is adopted by the ARB for medium-duty SULEVs, the manufacturer has agreed to a default value listed below.

NMOG FLEET AVERAGE [g/mi]  RAF = 1.00			G [g/mi] F = 1.00	CH4 = methane NMOG = non-CH4 organic gas NMHC = non-CH4 hydrocarbon CO = carbon monoxide NOx = oxides of nitrogen HCHO = formaldehyde PM = particulate matter RAF = reactivity adjustment factor												
CERT	CERT STD		CH4 RAF ≈ 0.0047		CO [g/mi]			NOx [g/mi]		HCHO [mg/mi]		Р	PM [g/mi]		Hwy NOx [g/mi]	
0.053	0.06	88	CERT	CERT STD		STD	С	ERT	STD	CERT	STD	CER	г ѕ	TD	CERT	STD
K = 1000 miles	@	50K	*	* *		*		*	*	*	*	*		*	*	*
	@ '	120K	0.001	0.010	0.1	1.0	(	0.01	0.02	0.1	4	*		*	0.01	0.03
	@ 50°F	F, 4K	*	*	*	*		*	*					*	*	
CO [g/mi] g = gram mg = milligra					NMHC+NOx [g/mi] (composite)			NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]			NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
CERT	ST			mi = mile		STD	С	ERT	STD	CERT	STD	CERT		TD	CERT	STD
*	*	*		@ 4K		*	*		*	*	* *		*		*	*
F = degree Fahrenheit			@ 120K		*	*		*	*	. *	*	*		*	*	*
@	EVAPORATIVE FAMILY 1			EVAPORATIVE FAMILY 2				VAPORATIVE FAMILY 3			EVAPORATIVE FAMILY 4					
120K	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	*	*	*	*	*	*	*	•	*	*	*	*	*	*	*	*
STD	*	*	*	*	*	*	*	*	*	*	*		•	*	. *	
2-D, 3-D [g/	test] = 2-c	lay, 3-d	lay diurnal	and hot-soak		RL [g/mi]	= runni	ng loss		ΦRVR [g/g:	allon of fu	el dispense	d] = on-b	oard refue	ling vapo	r recovery

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

**BE IT FURTHER RESOLVED:** That the listed vehicle models have been certified to meet the requirements in 13 CCR Section 1962 (c)(2) and are hereby granted a partial zero-emission-vehicle (PZEV) allowance of 0.4

/ehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of September 2001.

P. B. Summerfield, Chief Mobile Source Operations Division