Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

	MODEL YEAR TEST GR			VEHICLE TYPE		AUST EMISSION PARD CATEGORY	FUEL TYPE				
2002	2 2HNX	2HNXV02.0DYC		Passenger Car	Low E	Emission Vehicle (LEV)	Gasoline				
No.		EVAPORATIVE FAMILY (EVAP)		SPECIAL FEATUREMISSION CONTROL S	URES & SYSTEMS (ECS)	* = not applicable	TWC = 3-way catalytic converter WUTWC = warm-up TWC OC = oxidation catalytic converter O2S				
1	2HNXR013	KR0130AAF			S(2), AIR, SFI, OBD	oxygen sensor AFS/HAFS = air/fuel sensor (aka. Universal O2S)/ heated AFS HO2S = heated O2S EGR = exhaust gas recirculation AIR = secondary air injection PAIR = pulsed AIF MFI = multiport fuel injection SFI = sequential MFI					
2	*	•			*						
3	*	•			*						
4	*	*			*	TC/SC = turbo/super charger CAC = charge air cool OBD (F) / OBD (P) = on-board diagnosis; full / partial compliance (prefix) 2 = parallel (2) (suffix) = serie					
EVAF No.	P ECS No.	ENGINE SIZE (L		VEHICLE MAKES & MODELS	VEHICLES SUB- STANDARDS AR		ABBREVIATIONS:				
1	1	2.0									
*	*	* *				*					
*	*	* *				*					
*	*	* *		1		. *	And the state of t				

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

	MOG FLEET ERAGE [g/mi] T STD		NMOG [g/mi] @RAF = 0.94 CH4 RAF = *		CH4 = methane NMOG = non-CH4 organic gas NMHC = non-CH4 hydrocarbon CO = carbon monoxide NOx = oxides of nitrogen HCHO = formaldehyde PM = particulate matter RAF = reactivity adjustment factor												
CERT					CO [g/mi]			NOx [g/mi]		HCHO [mg/mi]			PM [g/mi]		Hwy NOx [g/mi]		
0.053	0.06	8	C	ERT	STD	CERT	STD	CI	ERT	STD	CERT	STD	CERT		TD	CERT	STD
K = 1000 miles	@	50K	0.	.036	0.075	0.5	3.4	(	0.1	0.2	1	15			*	0.02	0.3
	@ 1	00K	0.	0.042 0.090		0.6	4.2	0.1	0.1	0.3	1	18	*	-	*	0.03	0.4
	@ 50°F	, 4K		*	*	*	*		*	*	*	*	*		*	*	*
	[g/mi] PF, 50K		g = gram mg = milligram			NMHC+NOx [g/mi] (composite)		NN	NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMH	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
CERT	STE	)		mi = mile		CERT STD		C	ERT	STD	CERT STD	CER		STD	CERT	STD	
2.1	10.0			@ 4K		*	*	•		*	*		*	*		*	*
F = degree	Fahrenhe	it	@ 100K		*	*		*	•	*	*	*		*	*	*	
@	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EV				APORATIVE FAMILY 3			EVAPORATIVE FAMILY 4					
100K	3-D	2-D	- [	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	1.0	1.1		0.01	0.02	*	*	*	*	*	*	*	*	*	*	*	*
STD	2.0 2.5			0.05	0.20	*	*	*	*	*	*	*	*	*	*		*
2-D, 3-D [g/	test] = 2-d	ay, 3-d	ay di	iurnal aı	nd hot-soak		RL [g/mi]	= runnir	ng loss	-,	ORVR [g/ga	illon of fu	el dispense	d] = on-b	oard refu	Jeling vapo	r recovery

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of September 2001

R. B. Summerfield, Chief Mobile Source Operations Division