HYUNDAI MOTOR COMPANY

EXECUTIVE ORDER A-254-0075 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

	MODEL YEAR TEST G			VEHICLE TYPE		UST EMISSION ARD CATEGORY	FUEL TYPE					
2002	2HYX	2HYXV01.5ALS		Passenger Car	Low E	mission Vehicle (LEV)	Gasoline					
No.		APORATIVE MILY (EVAP)		SPECIAL FEATURES EMISSION CONTROL SYSTEM		TWC = 3-way catalytic converter WUTWC = warm-up TWC OC = oxidation catalytic converter O2S						
1	2HYXR010	5PEA	1	TWC, HO2S(2)	SFI, OBD (F)	oxygen sensor AFS/HAFS = air/fuel sensor (ak Universal O2S)/ heated AFS					
2	*		2	*		HO2S = heated O2S EGR = exhaust gas recirculation						
3	*		3	*			AIR = secondary air injection PAIR = pulsed AIR MFI = multiport fuel injection SFI = sequential MFI					
4	*		4	*		TC/SC = turbo/super charger CAC = charge air cool OBD (F) / OBD (P) = on-board diagnosis; full / partial compliance (prefix) 2 = parallel (2) (suffix) = serie						
EVAI No.	P ECS No.	ENGINE SIZE (L				ECT TO SFTP	ABBREVIATIONS:					
1	1	1.5										
*	*	*			#							
*	*	* *			······································	*						
*	* * *					*						

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

AVERA	G FLEET AGE [g/mi] STD		NMOG [g/mi] @RAF = 0.94 CH4 RAF = *			CH4 = methane NMOG = non-CH4 organic gas NMHC = non-CH4 hydrocarbon CO = carbon monoxide NOx = oxides of nitrogen HCHO = formaldehyde PM = particulate matter RAF = reactivity adjustment factor											
CERT						CO [g/mi]			NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]			Hwy NOx [g/mi]	
0.058	0.0	0.068		ERT	STD	CERT STD		CE	CERT		CERT	STD	CER	T S	TD	CERT	STD
K = 1000 miles	@	@ 50K		0.032	0.075	0.3	3.4	3.4 0.1		0.2	1	15	*		•	0.04	0.3
	@ 100K		O	.034	0.090	0.3 4.2		C	0.1	0.3	2	18	*		*	0.05	0.4
	@ 50°	F, 4K 0.11		.113	0.150	0.8	3.4	3.4 0.1		0.2	1	30	•		*	. *	*
	[g/mi] °F, 50K			g = gram mg = milligram mi = mile		NMHC+NOx [g/mi] (composite)		NM	NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMH	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
CERT	ST	STD				CERT	STD	CE	RT	STD	CERT		CER	T S	TD	CERT	STD
3.5	10.	10.0		@ 4K		*	*	*		*	*.	*	•			*	*
F = degree	Fahrenh	eit			@ 100K	*	*		*	*	*	*	*		*	*	•
@ 100K	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 E				EV	VAPORATIVE FAMILY 3			EVAPORATIVE FAMILY 4				
	3-D	2-D	,	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	0.5	0.9		0.02	0.02	*	*	*	*	*		*	*	*	•	*	*
STD	2.0	2.5		0.05	0.20	*	*	*	*		*	*	*	*	*		*
2-D, 3-D [g/	test] = 2-	day, 3-c	lay c	liurnal a	nd hot-soak		RL [g/mi] =	runnir	g loss		ORVR [g/ga	illon of fue	dispense	d] = on-b	oard ref	ueling vapo	r recovery

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California explications. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _

_ day of August 2001.

R. B. Summerfield, Chief Wobile Source Operations Division