**EXECUTIVE ORDER A-030-0139-2** 



New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR TEST GROUI				_	VEHICLE TYPE PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	CATEGOR vehicle:	EMISSION STANDAI Y (LEV=low emiss: TLEV= transitional LEV; LEV; SULEV=super ULE	Ion EVAPORATIVE USEFUL LIFE	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200	2002 2ADXV01.8342			2	PC		ULEV	100K / 100K	Gasoline (Indolene)				
No.		VAPORATIVE AMILY (EVAF)		No	SPECIAL FEATURES EMISSION CONTROL SYSTI			OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S					
1	2AD	2ADXR0140232			TWC, HO2S(2), AIR,		AFS/HAFS=air-fuel ratio s	sensor/heated AFS_EGR=exhaust					
2	2AD	2ADXR0140262				*	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board						
3		•				*							
4		*				*	diagnostic prefix 2=para	OBD (F) / (P)=full /partial on-board					
EVAF No.		CS No.	ENGINE SIZE (L)				ECT TO SFTP	19					
1	<u> </u>	1 1.8		MARCS & MODELS   ST	AKES & MODELS STANDARDS ARE UNDERLINED VOLKSWAGEN Passat Sedan / Wagon								
2	1 1.8			$\top$	AUDI A4 Sedan / Quattro Sedan / Avant Quattro Wagon								
*		*	*		Sauce o reagon								
*		*	*		•								

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows; compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NM AVE	NMOG FLEET NN AVERAGE [g/mi]		NMOG @ RAF=1.00 CH4 RAF = *		NMOG or	Introgen	HUNUTIO	maidehyda	PM=par	ticulate m	12tter	RAFeroscik	itu adinetm	arbon mono	2/2 12 [-/44	1-2/2 4
CER	T	1411100			NMHC	mg=millig	UL-SOAK K	ւ լց/ույ≃ու	ning loss 000 miles	ORVR	g/gallon	dispensed] hrenheit	=on-board ı	efueling vap	or recovery	g≕gram
0.06	1	0.068	CERT	CERT	[g/mi]		[g/mi]		x [g/mi]			mg/mi]		g/mi]	Hwy NO	
			[g/mi]	[g/mi]	13	CERT	STD	CERT	STI	D C	ERT	STD	CERT	STD	CERT	STD
4		@ 50K	0.024	*	0.040	1.0	1.7	0.04	0.2	2 (	0.2	8	*	•	0.01	0.3
		@ UL	0.029	*	0.055	1.2	2.1	0.04	0.3		0.2	11	*	*	0.01	0.4
* #	@ 50	°F & 4K	0.049	*	0.080	1.1	1.7	0.02	0.2	: (	0.2	16	*	*	*	*
@ 20	CO [g/mi] @ 20°F & 50K		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV					g/mi] oosite)	NMHC+NO [g/mi] [US0		1	O [g/mi] [US06]	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
50			SFTP 2 = @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	STD	CE	RT ST			CERT	STD
CERT	1.2		1	SFTP 1	*	*	*	*	0.10	0.14	6.	5 8.0	0.12	0.20	1.3	2.7
STD	10.0			SFTP 2	*	*	*	*	*	*	1	*	•	*	*	•
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2			EVAPORATIVE FAMILY 3				E	EVAPORATIVE FAMILY 4			
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVE		2-D	RL	ORVR
CERT	1.5	1.6	0.003	0.01	1.1	1.2	0.003	0.08	*	+	*	*	-	*	*	•
STD	2.0	2.5	0.05	0.20	2.0	2.5	0.05	0.20	*	*	*	-	+	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-030-0139-1 dated August 29, 2001.

23 day of January 2002. Executed at El Monte, California on this

R. B. Summerfield, Chief

Mobile Source Operations Division