



LOTUS CARS LIMITED

EXECUTIVE ORDER A-037-0032 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP		N N	VEHICLE TYPE C=passenger car; LDT=light-duty truck; DV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)		AUST EMISSION DARD CATEGORY	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)				
200	2 2	2LTXV03.5918			PC		Tier 1	100K / 100K	Gasoline (Indolene)				
No.		VAPORATIVE AMILY (EVAF)			SPECIAL FEATURES EMISSION CONTROL SYSTE		* = not applicable	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S					
1	2LTXR	₹0124	OVR	1	2TWC, 2HO2S(2), EGR,	AIR, SFI, 2TC	AFS/HAFS=air-fuel ratio	sensor/heated AFS EGR=exhaust					
2		•			1		gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI						
3		*			*		TBI= throttle body injection TC/SC=turbo /super charger						
4		*		4	1		CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
EVAI No.	EC No		ENGINE SIZE (L		VEHICLE VEI	HICLES SUBJ NDARDS AR	ECT TO SFTP	F4					
1	1		3.5				LOTUS ESPRIT V8						
*	*	* *											
*	*	•	+				*						
*	•		*										

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows; compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	AVERAGE [g/mi] C CERT STD N		NMOG @ CH4 RAF		NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram											
CE			D	NMOG	NMHC CERT [g/mi]	NMHC STD [g/mi]	mg=millig	ot-soak K	L [g/mi]≃rui	nning loss 1000 miles	ORVR	₹ [g/gallor	n dispensed] ahrenheit	=on-board r	efueling vap plemental fe	or recovery	g=gram
0.2			68	CERT [g/mi]			CO [g/mi]			NOx [g/mi]		нсно	[mg/mi]	PM [g/mi]		Hwy NOx [g/mi]	
							CERT	STD	CERT	r st	D	CERT	STD	CERT	STD	CERT	STD
			50K	*	0.09	0.25	1.3	3.4	0.1	0.4	1	*		*	*	0.01	0.5
			UL	*	0.12	0.31	1.9	4.2	0.2	0.6	3	*	*	*	*	0.01	0.8
	(@	50°F 8	& 4K	*	•	•			*	*		*	•	*	*	*	•
@ 2	CO [g/mi] @ 20°F & 50K		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV SFTP 2 = @ UL (Tier 1, TLEV)		ier 1, TLEV 🗌	NMHC+NOx [g/mi] (composite)		CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]				HC+NOx ii] [SC03]	CO [g/mi] [SC03]		
					1, TLEV)	CERT	STD	CERT	STD	CERT	STE) CE	RT STI	CER	T STD	CERT	STD
CER	T 3.	8			SFTP 1	0.24	0.65	*	*	*	*	1.	.3 9.0		*	0.2	3.0
STD	10.	.0		37 mil	SFTP 2	0.28	0.91	*	•	*	*	1.	9 11.	1 *	•	0.2	3.7
@ UL	L	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2			EVA	EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
	3	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV	₹ 3-D	2-D	RL	ORVR
CER	T 1	1.5	1.2	0.002	0.06	*	*	*	*	*	*	*	*	*	•	*	•
STD	2	2.0	2.5	0.05	0.20	*	*	*	*	*	*	*	•	*		*	•

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

__ day of January 2002.

CR. B. Summerfield, Chief

Mobile Source Operations Division