Fieli



MITSUBISHI MOTORS CORPORATION

EXECUTIVE ORDER A-086-0252 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI YEA		TEST GROUP  2MTXV01.5GND			VEHICLE TYPE		UST EMISSION ARD CATEGORY	FUEL TYPE					
200	2 2M				Passenger Car	Low E	Emission Vehicle (LEV)	Gasoline					
No.	EVAPOR FAMILY			No.	SPECIAL FEATUR EMISSION CONTROL SYS		* = not applicable	TWC = 3-way catalytic converter WUTWC = warm-up TWC ADSTWC = adsorber TWC OC = oxidation					
1	2MTXR0	140A1A	. I	1	WUTWC, TWC, HO	2S(2), SFI, EGR,	catalytic converter O2S = oxygen sensor HO2S = heated O2S						
2		•				±	AIR = secondary air injection PĀIR = pulsed AIR   MFI = multiport fuel injection SFI = sequential MFI   TC/SC = turbo/super charge						
3	*	3				4							
4						*	compliance (prefix) 2 = parallel (2) (suffix) a seri						
EVAI	P ECS		GINE E (L)		VEHICLE MAKES & MODELS	VEHICLES SUB	JECT TO SFTP RE UNDERLINED						
1	1 1		.5		MITSUBISHI MIRAGE								
*			*		•								
•	•			-	•								
			•		*								

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

NMOG FLEET AVERAGE [g/mi]			NMOG [g/mi] @RAF = 0.94		CH4 = methane NMOG = non-CH4 organic gas NMHC = non-CH4 hydrocarbon CO = carbon monoxide NOx = oxides of nitrogen HCHO = formaldehyde PM = particulate matter RAF = reactivity adjustment factor											
CERT			CH4 RAF = *		CO [g/mi]		NO	NOx [g/ml]		HCHO [mg/ml]		PM [g/mi]			Hwy NOx [g/ml]	
0.061			CERT	STD	CERT	STD	CERT	RT	STD	CERT	STD	CERT	ST	D	CERT	STD
K = 1000 miles	@	50K	0.038	0.075	0.2	3.4	0.1		0.2	0.4	15	*	1	•	0.03	0.3
	@1	00К	0.045 0.090		0.3	4.2	0.1	_	0.3	0.4	18	*	,	•	0.03	0.4
HIIIES	@ 50°F	, 4K	0.102	0.150	1.6	3.4	0.1	1 0.2	0.2	0.5	30	*	,	*	*	*
CO [g/mi] @ 20°F, 50K			g = gram mg = milligram		NMHC+NOx [g/mi] (composite)			NMHC+NOx [g/ml] [US06]		CO [g/mi] N [US06]			NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
CERT	STD		mi = mile		CERT	STD	CERT		STD	CERT	STD	CERT	r s	TD	CERT	STD
3.4	10.0			@ 4K		•	•		•	*	•			•	*	*
F = degree	Fahrenhe	ahrenheit		@ 120K		•	•		•		•		•	*	•	
<u> </u>	EVAPORATIVE FAMILY 1			EVAPORATIVE FAMILY 2 E				EV	VAPORATIVE FAMILY 3			EVAPORATIVE FAMILY 4				
@ 100K	3-D 2-D		RL	ORVR	3-D	2-D	RL (	ORVR	3-D ·	2-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	0.6	0.7	0.03	0.01	•	*	*	+	•	*	•	•	*	*	*	*
STD	2.0 2.5		0.05	0.05 0.20		•	•	*	•	*	•	•	•	•	•	•
2-D, 3-D [g/	test] = 2-d	lay, 3⊰	day diurnal	and hot-soal	recovery	RL	g/mi] = rur	nning k	055	ORVR [g/g	allon of fue	dispense	d] = on-bo	oard refu	eling vapo	r recovery

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_\_ day of June 2001. \_\_\_\_\_\_\_\_\_

R. B. Summerfield, Chief Mobile Source Operations Division