

MITSUBISHI MOTORS CORPORATION

EXECUTIVE ORDER A-086-0254 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP			VEHICLE TYPE		AUST EMISSION DARD CATEGORY	FUEL TYPE				
200	2 2N	ITXV	02.0GN	ıG	Passenger Car	Low I	Emission Vehicle (LEV)	Gasoline				
No.	EVAPORATIVE FAMILY (EVAP)		No.	SPECIAL FEATURES EMISSION CONTROL SYSTE		* = not applicable	TWC = 3-way catalytic converter WUTWC = warm-u TWC ADSTWC = adsorber TWC OC = oxidatio					
1	2MTXR0	140A	MA	1	WUTWC, TWC, HO2S(2), SFI, EGR	catalytic converter O2S = oxygen sens HO2S = heated O2S EGR = exhaust gas recirculati					
2		•		2	1		AIR = secondary air injection PAIR = pulsed AI MFI = multiport fuel injection SFI = sequential MF TC/SC = turbo/super charger CAC = charge air coole					
3	,			3	•							
4		•			1		OBD (F) / OBD (P) = on-board diagnosis; full / partia compliance (prefix) 2 = parallel (2) (suffix) = set					
EVAI No.							JECT TO SFTP					
1	1	- [1.6		MITSUBISHI LANCER							
1	1		2.0		MITSUBISHI LANCER							
٠			•		•							
*	*	•			•							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

	FLEET NGE (g/mi]	@RAF	[g/mi] = 0.94		nethane ≖ oxides of	MOG ≃ no nitrogen			aldehyde		CH4 hydro iculate ma			arbon moi tivity adju	
CERT	STD		ČH4 RAF = *		CO [g/mi]		NC	NOx [g/mi]		HCHO [mg/ml]		PM [g/mi]			Hwy NOx [g/mi]	
0.061	0.06	8	CERT	STD	CERT	STD	CERT		STD	CERT	STD	CER	T ST	D.	CERT	STD
	@ 50K		0.035	0.075	0.3	3.4	0.1 0.1		0.2 0.3	1	15 18	*	*		0.1 0.1	0.3
K = 1000 miles	@ 100K		0.044	0.090									•	,		
	@ 50°F	, 4K	0.083	0.150	0.7	3.4	0.02		0.2	0.1	30	•	•		•	*
CO [g/mi] @ 20°F, 50K			g = gram mg = milligram		NMHC+NOx [g/mi] (composite)			NMHC+NOx [g/mi] [US06]		CO [g/mi] [U\$06]		NMH	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
CERT	ERT STD		mi = mile		CERT	STD	CERT		STD	CERT	STD	CER	T ST	D O	CERT	STD
3,0	10.0		@ 4K		•	•	•		•	*	•	•	•		•	*
F = degree	Fahrenheit		@ 120K	•	•	*		•	•	•	•	•		*	*	
@	EVAPORATIVE FAMILY 1			EVAPORATIVE FAMILY 2 E			EV	VAPORATIVE FAMILY 3			EVAPORATIVE FAMILY 4					
@ 100K	3-D	2-D	RL	ORVR	3-D	2-D	RL C	RVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	1.4	2.0	0.02	0.02	•	*	•	*	*	•	•	*	*	*	*	•
STD	2.0	2.5	0.05	0.20	•	4	•	•			•	•	•	•	1.	•

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 1874 day of June 2001.

A. B. Summerfield, Chief Mobile Source Operations Division