

HYUNDAI MOTOR COMPANY

Frel

EXECUTIVE ORDER A-254-0079 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| MODE YEAR | | | | VEHICLE TYPE | EXHAUST EMISSION STANDARD CATEGORY | | | FUEL TYPE | | | | |
|--------------|--------------|----------------------------|---|---|---------------------------------------|-------------------------|------------|--|--|--|--|--|
| 2002 | 2 2HYX | T02.7MLS | 6 | 3751-5750 Pounds Loaded Vehicle Weight Light Duty Truck | Low Emission Vehi (LEV) | | /ehicle | Gasoline (Indolene) | | | | |
| No. | | VAPORATIVE AMILY (EVAP) | | SPECIAL FEATURES 8 EMISSION CONTROL SYSTEM | IS (ECS) | (ECS) *= not applicable | | TWC = 3-way catalytic converter WUTWC = warm-up TWC OC = oxidation catalytic converter | | | | |
| 1 | 2HYXR017 | 75PES | 1 | TWC, 2HO2S(2), 2WU | TWC, SFI, OE | 3D (F) | | WUOC = warm-up OC O2S = oxygen senso | | | | |
| 2 | * | | 2 | | | HO2S = heated O2S | | | | | | |
| 3 | * | | 3 | | | | | MFI = multiport fuel injection SFI = sequential MFI TC/SC = turbo/super charger CAC = charge air cooler | | | | |
| 4 | * | | 4 | * | | | | OBD (F) / OBD (P) = on-board diagnosis; full / partial compliance (prefix) 2 = parallel (2) (suffix) = series | | | | |
| EVAF No. | P ECS No. | ENGINE SIZE (L | | | ICLES SUBJE | | | ABBREVIATIONS: | | | | |
| 1 | 1 | 2.7 | | | Hyu | ndai San | ta Fe 2WD/ | 4WD | | | | |
| * | * | | | | | | * | 1771-1 17 | | | | |
| * | * | * * | | | | | * | | | | | |
| * | * | * | | | | | * | | | | | |

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

| | OG FLEET RAGE [g/mi] STD | | NMOG [g/mi] @RAF = 1.00 CH4 RAF = * | | | CH4 = n NOx = o | ethane xides of n | NMOG = itrogen | | l4 organic = formald | | | CH4 hydro | | | carbon mo | |
|-----------------------------------|--------------------------------|----------|---|--|-------------------------|--------------------|----------------------|-------------------|--------------------|-------------------------|---------------------------|-------------|----------------------|-----------|----------|----------------|------------|
| CERT | | | | | | CO [g/mi] | | | NOx [g/mi] | | HCHO [mg/mi] | | F | PM [g/mi] | | Hwy NOx [g/mi] | |
| 0.100 | 0.095 | | CERT | | STD | CERT | STE | CI | ERT | STD | CERT | STD | CER | T S | STD | CERT | STD |
| K = 1000 miles | @ | 50K | C | 0.049 0.100 | | 0.9 | 4.4 0.01 | | .01 | 1 0.4 | 0.2 | 18 | 18 * | * | | 0.04 | 0.5 |
| | @ | 100K | C | 0.053 | 0.130 | 1.1 | 5.5 4.4 | | 0.01 | 0.5 | 0.2 | 23 36 | * | | * | 0.05 | 0.7 |
| | @ 50°l | F, 4K | C | 0.155 | 0.200 | 1.2 | | | | | | | * | | * | | |
| CO [g/mi] g = gram mg = milligram | | | | NMHC+NOx [g/mi] NMHC+NOx [g/mi] (composite) [US06] | | | | CO [g/mi] N | | | NMHC+NOx [g/mi] [SC03] | | CO [g/mi] [SC03] | | | | |
| CERT | STD 12.5 | | mi = mi | | | CERT | STE | CE | ERT | STD | CERT | STD | CER | | STD | CERT | STD |
| 8.1 | | | | | @ 4K | * | * | | * | * | | * | * | | * | * | * |
| F = degree Fahrenheit | | | @ 100K | | * | * | | * | * | * | * | * | | * | * | * | |
| @ | EVAPORATIVE FAMILY 1 | | | | EVAPORATIVE FAMILY 2 EV | | | | APORATIVE FAMILY 3 | | | | EVAPORATIVE FAMILY 4 | | | | |
| 100K | 3-D | 2-D | | RL. | ORVR | 3-D | 2-D | RL | ORVR | 3-D | 2-D | RL | ORVR | 3-D | 2-D | RL | ORVR |
| CERT | 0.7 | 2.1 | | 0.004 | 0.04 | * | * | * | • | • | * | * | * | * | * | * | * |
| STD | 2.0 | 2.0 2.5 | | 0.05 | 0.20 | * | * | * | | + • | • | * | * | • | * | * | * |
| 2-D, 3-D [g/ | test] = 2-c | lay, 3-d | lay o | diurnal ar | nd hot-soak | 1. | RL [g/mi |] = runnin | g loss | | ORVR [g/ga | llon of fue | dispense | d] = on-b | oard ref | ueling vapo | r recovery |

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order

Executed at El Monte, California on this

day of August 2001

R. B. Summerfield Chief
Mobile Source Operations Division