

MITSUBISHI MOTOR MANUFACTURING OF AMERICA, INC.

EXECUTIVE ORDER A-292-0058 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR TEST GROUP			VEHICLE TYPE		AUST EMISSION ARD CATEGORY	FUEL TYPE								
200	2 20	2DSXV02.4GNG			Passenger Car	Low E	Emission Vehicle (LEV)	Gasoline						
No.		RATIVE (EVAP)		No.	SPECIAL FEATURES & EMISSION CONTROL SYSTEM		* = not applicable	TWC = 3-way catalytic converter WUTWC = warm-up TWC ADSTWC = adsorber TWC OC = oxidation						
1	2DSXR0165A1F			1	WUTWC, TWC, H02S(2)	, EGR, SFI,	OBD (F)	catalytic converter O2S = oxygen sensor HO2S = heated O2S EGR = exhaust gas recirculation						
2		•			•		AIR = secondary air injection PAIR = puised AIR							
3		•		3	•			MFI = multiport fuel injection SFI = sequential MF TC/SC = turbo/super charger CAC = charge air coole						
4				4	•		OBD (F) / OBD (P) = on-board diagnosis; full / partial compliance (prefix) 2 = parallel (2) (suffix) = seri							
EVAF No.	ECS No.		SINE E (L)				JECT TO SFTP							
1	1	2	.4		MITSUBISHI ECLIPSE, E	CLIPSE SP	YDER, GALANT; CHE	RYSLER SEBRING; DODGE STRATUS						
	*			1	•									
*	•			1	*									
•	*	ļ,		1			*							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows. Any debit in the manufacturer's compliance plan for "NMOG Fleet Average" (passenger cars and light-duty trucks) or "Vehicle Equivalent Credit" (medium-duty vehicles) shall be equalized as required. The 50° Fahrenheit standards and CERT levels are listed below or compliance has been met based on the manufacturer's submitted compliance plan in lieu of actual testing.

NMO0 AVERA	G FLEET AGE (g/m	ni]		@RAF	[g/mi] = 0.94		nethane = oxides o	NMOG of nitrog		14 organic CHO = form	aldehyde		CH4 hydro liculate ma			carbon moi ctivity adju		
CERT	CERT STD		CH4 RAF = *			CO [g/mi]			NOx [g	/mi]	HCHO [mg/mi]		F	PM [g/mi]			Hwy NOx [g/ml]	
0.061	0.0	0.068		ERT	STD	CERT	STD	С	ERT	STD	CERT	STD	CER	T S	OT	CERT	STD	
K = 1000 miles	Q.	50K	C	.024	0.075	0.3 0.4 0.7	3.4 4.2 3.4	C	3.04	0.2 0.3 0.2	1 1 0.2	15 18 30	•		•	0.04	0.3	
	@	100K	C	0.035	0.090 0.150				0.1						•	0.1	0.4	
	@ 50°	F, 4K	C	0.052				0.0	0.01									
	[g/mi] 9°F, 50K			g = gram mg = milligram mi = mile @ 4K		NMHC+NOx [g/ml] (composite)		I] NA	NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMH	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
CERT	ST					CERT *	STD	CERT		STD	CERT	STD	CERT	T S	TD	CERT	STD	
4.5	10.								•	•	*	•	+	•		•		
ř = degree	Fahrenh	elt			@ 120K	*	•		*	•	*	+	•		*	•	•	
@ 100K	EVAPORATIVE			E FAMILY 1		EVAPORATIVE F			FAMILY 2 E		/APORATI	VE FAMI	_Y 3	EV.	APORA	ATIVE FAMILY 4		
	3-D	2-D	,	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	
CERT	0.6	0.8		0.01	0.01	*	•	*		•	•	*	*	*		•	•	
STD	2.0	2.0 2.5		0.05	0.20	•			+		*	•	•	•		-	+ :	
2-D, 3-D [g/	test] = 2-	day, 3-c	lay (diurnal a	nd hot-soak	recovery	RL	[g/mi] =	running	loss	ORVR [g/g	illon of fue	dispense	d] = on-b	oard refu	ueling vapor	recovery	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 (labeling), 1968.1 or 1968.1(m)(6.2) (on-board diagnostic systems; full or partial compliance), 2035 et seq. (emission control warranty), 2235 (fuel tank fill pipes and openings), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles).

Vehicles certified under this Executive Order shall conform to all applicable California encission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of July 2001.

R. B. Summerfield, Chief Mobile Source Operations Division

v