

GENERAL MOTORS CORPORATION

EXECUTIVE ORDER A-006-1086-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP			ME	VEHICLE TYPE =passenger car; LDT=light-duty ti)V=medium-duty vehicle; LVW=loa ehicle weight; ALVW=adjusted LV	CATEGORY vehicle; T	EMISSION STANDA (LEV=low emis: LEV= transitional LEV LEV; SULEV=super UL	slon	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)					
200	3	3GMXT03.0162				LDT: 3,751-5,750 pounds LVV		LEV		100K / 100K Gasoline						
No.		EVAPORATIVE FAMILY (EVAF)				SPECIAL FEATU EMISSION CONTROL S			* = not applicable	oc	C/TWC=oxidizing/3-way J= warm-up cat. O2S/F	cat. ADSTWC=adsorbing TWC IO2S=oxygen sensor/heated O2S				
1	3GM	3GMXR0124919			1	SFI, 2WUTWC,	TWC,	2HO2S(2), OI	AFS/HAFS=air-fuel ratio sensor/heated AFS_EGR=exhaust							
2		*			2		*		Alf	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI						
3		*			3	•					TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board					
4		*		-	•		*		dia	diagnostic prefix 2=parallel (2) suffix=series						
EVAI No.		ECS No.	ENGIN SIZE (L			VEHICLE MAKES & MODELS					ABBREVIATIONS: *					
1		1 3.0 Saturn VUE AWD/F								<u>VD</u>	D					
•		•	*													
*	* *					•										
*	*		*													

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]			NMOG @ CH4 R	RAF=0.94 AF = *	NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day djurnal+hot-soak R L [g/mi]=running loss ORVR [g/gallon dispensed]=on-dard refueling vapor recovery g=gram											
CER	CERT STD		NMOG	NMHC	NMHC STD	mg=milligram mi=mile K=1000 miles F=degrees Fahrenheit SFTP=supplemental federal test procedure											
0.07		.093	CERT	CERT	[g/mi]	CO	CO [g/mi]		NOx [g/mi]		НСНО	[mg/mi]	PM [PM [g/mi]		Hwy NOx (g/mi)	
0.07	0.093		[g/mi]	[g/mi]	[9/111]	CERT	STD	CER	T S1	D C	ERT	STD	CERT	STD	CERT	STD	
		@ 50K	0.064	*	0.100	1.3	4.4	0.1	0.	4	1	18	*	*	0.05	0.5	
		@ UL	0.064	*	0.130	1.3	5.5	0.1	0.	5	1	23	*	*	0.05	0.7	
	@ 50°	F & 4K	*	*	*	*	*	*	1	'	*	*	*	*	*	*	
CO [@ 20		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV) SFTP 2 = @ UL (Tier 1, TLEV)			NMHC+N (comp		CO [g/mi] (composite)			NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50					CERT	STD	CERT	STD	CERT	STD	CE	RT ST	D CER	T STD	CERT	STD	
CERT	8.0			SFTP 1	*	*	*	*	0.07	0.25	3	.4 10.	5 0.04	0.27	1.0	3.5	
STD	12.5			SFTP 2	*	*	*	*	*	1			*	*	*	*	
@ LII	E	VAPOR	ATIVE FAN	ILY 1	EVAPORATIVE FAMILY 2 EVAP					APORATIVE FAMILY 3			E	EVAPORATIVE FAMILY 4			
@ UL	3-D	2-[) RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RI	ORV	R 3-D	2-D	RL	ORVR	
CERT	0.6	0.7	7 0.00	0.02	*	*	*	*	*	*	*	•	*	*	*	•	
STD	2.0	2.5	5 0.05	0.20	*	*	*	•	٠	*	*	*	*	*	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-006-1086 dated March 21, 2002.

Executed at El Monte, California on this 2074 day of June 2002.

Allen Lyons, Chief

Mobile Source Operations Division