GENERAL MOTORS CORPORATION

EXECUTIVE ORDER A-006-1091 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR TEST G			T GROUP	, (VEHICLE TYPE PC=passenger car; LDT=light-duty truc MDV=medium-duty vehicle; LVW=loade vehicle weight; ALVW=adjusted LVW)		AUST EMISSION DARD CATEGORY	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
2003 3GMXT03.414				1	LDT: 3,751-5,750 pounds LVW	Low E	Emission Vehicle (LEV)	100K / 100K	Gasoline				
No.			PRATIVE Y (EVAF)		SPECIAL FEATURE EMISSION CONTROL SYS	S & TEMS (ECS)	* = not applicable	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust					
1	3GM	XR01:	33910	1	SFI, TWC, HO	S(2), EGR, OBD							
2	3GMXR0175922			2		*	gas recirculation AIR/P	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI					
3	3GM	3GMXR0212923				*	TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
4		*				*							
EVAI No.		ECS ENGINE No. SIZE (L)				/EHICLES SUBJ TANDARDS AR	ECT TO SFTP E UNDERLINED	ABBREVIATIONS:					
1	1 3.4			Buick Rendezvous FWD/AWD; Pontiac Aztek FWD/AWD									
2		1 3.4			Chevrolet Venture FWD; Pontiac Montana FWD								
3		1 3.4			Chevrolet Venture FWD/AWD; Pontiac Montana FWD/AWD; Oldsmobile Silhouette FWD/AWD								
*					•								

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET AVERAGE [g/mi] CERT STD		NMOG @ RAF=0.94 CH4 RAF = *			CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCH0=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/ml]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram												
CERT				NMHC	NMHC STD [g/mi]	mg=millig	10t•soak F gram mi	t∟ (g/mij=n =mile K=	unning :1000 m	loss QF iles	₹VR [g/gal F≖degree:	lon disp s Fahre	oensed]=c nheit S	on-board re SFTP≃supp	fueling var lemental fe	or recover	y g≕gram rocedure	
0.078	0.093		CERT CI				[g/mi]		Ox [g/	/mi] H		HCHO [mg/mi]		PM [g/mi]		Hwy NO		
			",	[g/mi]	10 .	CERT	STD	CER	lT	STD	CERT	S	TD	CERT	STD	CERT	STD	
	@ 501	50K 0.045		•	0.100	1.0	4.4	0.2	:	0.4 1		18		*	*	0.1	0.5	
14	@ UL	0.05	51	•	0.130	1.3	5.5	0.2		0.5		-	23	•	*	0.2	0.7	
551	@ 50°F & 4H	*		*	*	•	*	*		*	•		*	•	*	*		
	0 [g/mi] 0°F & 50K		mg =			NMHC+NOx [g/mi] CO [g/mi] (composite)				IHC+NC				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
CERT	STD		milligram mi = mile		CERT	STD	CERT	STD	CER	T S	TD C	ERT	STD	CERT	STD	CERT	STD	
8.3	12.5	32	SFTP	@ 4K	*	*	*	*	0.09	0.	25	3.8	10.5	0.05	0.27	0.8	3.5	
F = degre	e Fahrenheit	SFTP @ UL		@ UL	*	*	*	*	*	,	•	*	*	•		*	•	
@ UL	EVAP	EVAPORATIVE FAMILY 1			EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3					EVAPORATIVE FAMILY 4				
<u></u>	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-0) 2	-D	RL	ORVR	3-D	2-D	RL	ORVR	
CERT	1.2	1.2	0.00	0.09	0.5	0.8	0.00	0.01	0.5	, 0	.9 (0.00	0.14	•	*	*	•	
STD	2.0	2.5	0.05	0.20	2.0	2.5	0.05	0.20	2.0) 2	.5 (0.05	0.20	*		 	•	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _574 day of February 2002.

Allen Lyons, Chief

New Vehicle/Engine Programs Branch