Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE				́l`м	VEHICLE TYPE C=passenger car; LDT=light-duty truck; DV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	CATEGORY	EMISSION STANDAF ( (LEV=low emissi 'LEV= transitional LEV; LEV; SULEV=super ULE	on USEFUL LIFE	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)					
2003	3	3VW)	VXT02.8225		LDT: 3,751-5,750 pounds LVW		TLEV	100K / 100K	100K / 100K Gasoline					
No.		VAPORATIVE AMILY (EVAF)		No.	SPECIAL FEATURES EMISSION CONTROL SYSTE	MS (ECS)	* = not applicable	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing T WU= warm-up cat. O2S/HO2S=oxygen sensor/heated						
1		3VWXR0140233			TWC, HO2S(2), A	IR, SFI, OBD	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AiR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series							
2	•			2										
3		•				•								
4		*				•								
EVA		ECS ENGINE			MAKES & MODELS STA	NDARDS AR	E UNDERLINED   -	ABBREVIATIONS: *						
No.	No. SIZE (L 1 2.8		-	VOLKSWAGEN EUROVAN: VR6 CAMPER, MV, MV POP TOP + W . P., GLS VAN										
-	* *				•									
*	-+	*	*	_	-									
-	+ +		$\dashv$	*										

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF=0.98 AVERAGE [g/mi] CH4 RAF = *			=0.98 = *	NMOG or NMHC	CH4=metha nitrogen diurnal+ho	HCHO=for t-soak Rl	maidehyde _ [g/mi]=run	PM=parti ning loss	culate ma ORVR [g/	atter /gallon	dispensed]	/ity aujusuii l=on-board r	arbon mono ent factor 2 efueling vap	or recovery	g=gram			
CERT	r s	TD	NMOG NMHC CERT CERT		STD	mg=milligr	am mi= g/mi]		ille K=1000 miles F		F≃degrees Fahrenheit HCHO [mg/ml]		SFTP=supplemental fo		Hwy NOx [g/mi]			
0.160	0.	.093	[g/mi]		g/mi]	[g/mi]	CERT	STD	CERT			RT	STD	CERT	STD	CERT	STD	
6.2		@ 50K	0.081	-	*	0.160	0.8	4.4	0.1	0.7	0	.0	. 18	*	*	0.00	0.9	
		@ UL	0.090	<del> </del> -	*	0.200	0.9	5.5	0.1	0.9	0	.0	23	*	*	0.00	1.2	
	200		0,230		*	0.320	2.6	4.4	0.1	0.7		2	36	*	*	*	*	
	CO [g/mi]   SFTP1=0			= @ 4K (SULEV, ULEV,			NMHC+NOx [g/mi]		CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		IHC+NOx ni] [SC03]		[g/mi] C03]	
	@ 20°F & SFTP		_EV) or 50K (Tier 1, TLEV) 2 = @ UL (Tier 1, TLEV)			CERT	STD	CERT	STD	CERT	STD	CE	RT ST	D CER	T STD	CERT	STD	
CERT	4.4			91 8	SFTP 1	*	*	*	*	*	*		* *	*	*	*	*	
STD	12.5				SFTP 2	*	*	*	*	*	*		* *		•	•	*	
0.5	100	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EV				EVA	APORATIVE FAMILY 3			E	EVAPORATIVE FAMILY 4			
@ UL	3-D			ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RI	ORV		2-D	RL	ORVR		
CERT	1.3	1.			0.02	*	*	*	*	•	*	*		*		+ +		
STD	2.0	2.	5 0.	05	0.20	*	*	*	*	*	*	*						

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of May 2002.

Allen Lyons, Chief

Mobile Source Operations Division