## California Environmental Protection Agency AIR RESOURCES BOARD

## DAIMLERCHRYSLER AG

EXECUTIVE ORDER A-003-0249
New Passenger Cars, Light-Duty Trucks
and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)			EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)							
200	3 3	3MBXT03.71BI			ME	OV: 3,751-5,750 pounds A	LVW	ULEV			120K / 120K Gasoline				
No.		APORATIVE MILY (EVAF)				N	No. SPECIAL FEATURES & EMISSION CONTROL SYSTEM			(ECS)	* = not applicabl	e OC	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbin WU= warm-up cat. O2S/HO2S=oxygen sensor/heat		
1	3MBXE	MBXE0153NNZ			- 1	SFI, 2WUTWC, 2T	WC, 2HO2S(	2), AIR,	AF	FS/HAFS≕air-fuel ratio s	ensor/heated AFS EGR=exhaust				
2		*				7.	*		ga Δ1	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo/super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series					
3		*					*		TE						
4		*					*		dia						
EVAI No.	ECS ENGINE VEHICLE VEHICLES SUBJECT T No. SIZE (L) MAKES & MODELS STANDARDS ARE UND			ABB	ABBREVIATIONS: *										
1	1		3.2			MERCEDES-BENZ ML320									
1	1		3.7	T											
*	*		*		MERCEDES-BENZ ML350										
*	*	* *			*										

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET NMOG @ RAF=0.94 AVERAGE [g/mi] CH4 RAF = *			NMOG or	nitrogen	HCHO=for	rmaidehvde	: PM=par	ticulate m	atter	R∆F≡reactiv	rbon CO=c	nt factor	2/3 D In/toct	1-2/2 days		
CER	CERT ST		NMOG	NMHC	NMHC STD	mg=millig	x-soak K	L [g/mi]=rui	nning loss 1000 miles		g/galion	dispensed] ahrenheit	on-board resupp	efueling vap	or recovery	g≈gram	
		*	CERT [g/mi]	CERT [g/mi]	[g/mi]		[g/mi]		x [g/mi]	Н		mg/mi]	PM [c		Hwy NO		
ļ			[g/m]	[g/m]		CERT	STD	CERT	STI	) CE	ERT	STD	CERT	STD	CERT	STD	
		@ 50K	0.024		0.100	0.2	4.4	0.1	0.4	ا ر	0.5	9	*	*	0.01	0.8	
		@ UL	0.028	*	0.143	0.2	6.4	0.1	0.6	5 1		13	*	*	0.02	1.2	
	@ 50°	F & 4K	0.058	*	0.200	0.3	4.4	0.1	0.4		1	18	*	*	*	*	
	CO [g/mi] @ 20°F & 50K		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV) SFTP 2 = @ UL (Tier 1, TLEV)			Ox [g/mi] osite)	mi] CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]				NMHC+NOx [q/mi] [SC03]		CO [g/mi] (SC031		
50						STD	CERT	STD	CERT	STD	CE	RT ST	XX		CERT	STD	
CERT	1.1		J.	SFTP 1	*	*	*	*	0.03	0.40	6.	6 10.	5 0.005	0.31	0.3	3.5	
STD	12.5			SFTP 2	*	*	*	*	*	*	1	*	*	*		*	
@ UL		VAPOR/	ATIVE FAN	IILY 1	EVAPORATIVE FAMILY 2				EVA	PORATI	VE FA	MILY 3	E\	EVAPORATIVE FAMILY 4			
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVI	₹ 3-D	2-D	RL	ORVR	
CERT	0.6	1.0	0.02	*	*	*	*	*	*	*	*	•	*	*	*	*	
STD	2.0	2.5	0.05	*	*	*	*	*	*		*		+	+	*		

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 1874 day of July 2002.

Allen Lyons, Chief

Mobile Source Operations Division