DAIMLERCHRYSLER AG

EXECUTIVE ORDER A-003-0250 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD				N	VEHICLE TYPE C=passenger car; LDT=light-duty truck; IDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas;					
2003 3MBXT05.01B				ı	MDV: 3,751-5,750 pounds ALVW	LEV			120K / 120K	LPG=liquefied petroleum gas) Gasoline					
No.	FAN	APORATIVE MILY (EVAF)		No.	SPECIAL FEATURES EMISSION CONTROL SYSTEI	& VIS (ECS)	* = not applicable	ос	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing To						
1	3MB	XE015	SNNZ	_1	SFI, 2WUTWC, 2TWC, 2HC	2S(2), AIR, E	I%I YY U	≔ warm•un cat. O2S/H	O2S=oxygen sensor/heated O2S ensor/heated AFS EGR=exhaust						
2		*		2	*		gas	-∥gas recirculation AIR/PAIR≔secondary air injection/pulsed							
3		*		3	*	TI T			AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
4		•		4	*	· · · · · · · · · · · · · · · · · · ·									
EVAF	Ē	ECS	ENGINE		VEHICLE VEH	IIOLEA ALIE			give ite pietra z-para	ici (z) suilix-series					
No.			SIZE (L		•••••	TANDARDS ARE UNDERLINED			ABBREVIATIONS: *						
1	1		5.0	- 1	MERCEDES-BENZ ML500										
*	*		*			IVIE	NOEDES-BENZ ML	MLOUU							
*	\neg	*	*	+-			*								
*		* *		——		*									
				.			*								

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NM AVE	NMOG FLEET NMOG @ RAF=0.94 AVERAGE [g/mi] CH4 RAF = *			NMOG or	CH4=meth nitrogen	ane NMO HCHO=fo	G≃non-CH4	4 organic g e PM=pa	as NMH	IC=non-(CH4 hydroca RAF=reactiv	rbon CO=c	arbon mond	oxide NOx=	oxides of	
CER	CERT STD		NMOG CERT	NMHC CERT	NMHC STD	mg=millig	ram mi=	mile K=	1000 miles	F=d	legrees F	ahrenheit	on-board r SFTP=sup	efueling var	or recovery	OEGram
•	İ	*	[g/mi]	[g/mi]	[g/mi]	CERT	[g/mi]		NOx [g/mi]		нсно	[mg/mi]	PM [g/mi]	Hwy NC	
		@ 50K	0.024		0.160		STD	CER			CERT	STD	CERT	STD	CERT	STD
	L		0.024			0.2	4.4	0.03	0.4	1	1	18	*	*	0.01	0.8
		@ UL	0.027	*	0.230	0.2	6.4	0.04	0.6	3	2	27	*	*	0.02	1.2
	@ 50°F	F & 4K	0.044	*	0.320	0.3	4.4	0.03	0.4		1	36	*	*	*	*
@ 20	CO [g/mi] SFTP 1 = @ 4K (SULEV, U @ 20°F & LEV) or 50K (Tier 1,			er 1. TLEV)	NMHC+No (comp	Ox [g/mi] CO [g/osite) (compo				C+NOx (US06)			NMHC+NOx [g/mi] [SC03]		CO [g/mi]	
50	K	SFIP 2	= @ UL (Tier	1, TLEV)	CERT	STD	CERT	STD	CERT	STD	<u> </u>					203]
CERT	1.1			SFTP 1	*	*	*	*	0.08	0.40				0.31	CERT	STD
STD	12.5			SFTP 2	*	*	*	*	*	*			*	0.31	0.00	3.5
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				- E	/ABODAT	IVE FAMI	<u> </u>
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL					
CERT	0.6	1.0	0.02	•	*	*	*	*	*	*	- KL	. ORVI	3-0	2-D	RL	ORVR
STD	2.0	2.5	0.05	*	*	*	•	•	•	*				+	<u> </u>	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of July 2002.

Allen Lyons, Chief

Mobile Source Operations Division