DAIMLERCHRYSLER AG

EXECUTIVE ORDER A-003-0252 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						and the second s							
TEAR			ST GROUP		VEHICLE TYPE (PC=passenger car; LDT=light-duty MDV=medium-duty vehicle; LVW=lo vehicle weight; ALVW=adjusted L	truck; CATEGO	ST EMISSION STAND. DRY (LEV=low emile; TLEV= transitional LEV tra LEV; SULEV=super U	EVAPORATIVE	FUEL TYPE (CNG/LNG≖compressed/ liquefied natural gas; LPG≖liquefied petroleum gas)				
2003 3MBXT05.51TI				R	MDV: 5,751-8,500 pounds AL\	vw	LEV	120K / 120K					
No.		NPORA MLY (E	ATIVE EVAF)	No	SPECIAL FEATURE SPECIAL FEATUR FEATURE SPECIAL FEATURE SPECIAL FEATURE SPECIAL FEATURE SPECIAL	JRES & . SYSTEMS (ECS)	* = not applicable	OC/TWC=oxidizing/3-wa	cat. ADSTWC=adsorbing TWC				
1	3MB	BXE0187NNZ			SFI, 2WUTWC, 2TW		MAPS/MAPS=air-fuel ratio	HO2S=oxygen sensor/heated O2S sensor/heated AFS EGR=exhaust					
2		•				*	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MF/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
3		*				*							
4		*				*							
EVAF No.		ECS No.	ENGINI SIZE (L		VEHICLE MAKES & MODELS	VEHICLES SU STANDARDS	BJECT TO SFTP ARE UNDERLINED	ABBREVIATIONS: *					
1			5.5		MERCEDES-BENZ ML55 AMG								
*		*	*										
*.		* *			•								
*		*	*				*						

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bidual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NM AVE	NMOG FLEET AVERAGE [g/mi]		NMOG @ RAF=0.94 CH4 RAF = *		NMOG or							H4 hydrocai RAF=reactiv				
CER	T S	STD	NMOG NMHC		NMHC STD	diurnal+ho	W-acev V	- [Buin]-in	nning loss 1000 miles	UKVK	(LO/gailor	ı aıspensed):	≖on-board r	efueling vap	OF recovery	g=gram .
		•	CERT CERT		[g/mi]	CO [g/mi]		NC	x [g/mi]		HCHO	mg/mi]	SFTP=supplemental fe PM [g/mi]		Hwy NOx [g/mi]	
Service Company	***************************************		ra)	ranni	1 3	CERT	STD	CERT	ST	D	CERT	STD	CERT	STD	CERT	STD
		@ 50K	0.045	*	0.195	0.6	5.0	0.04	0.6	3	2	22	*	•	0.02	1.2
		@ UL	0.055	*	0.280	0.8	7.3	0.1	0.9	,	2	32	*	•	0.04	1.8
	@ 50°l	F & 4K	0.062	•	0.390	0.7	5.0	0.04	0.6	,	1	44	•	*	*	*
@ 20	@ 20°F &		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)		NMHC+NOx [g/mi] CO [g/i (composite) (composite)			NMHC+NOx [g/mi] [US06]		CO [g/mi] [US061		HC+NOx		[g/mi] C031		
50	K	SFTP 2 = @ UL (Tier		1, TLEV)	CERT	STD	CERT	STD	CERT	STE	CE	RT STE			CERT	STD
CERT	0.9			SFTP 1	*	*	. *	*	*		-		+		*	
STD	12.5			SFTP 2	*	*	*	*	•	•	_	• •	*	-	*	•
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2			EVAPORATIVE FAMILY 3			EVAPORATIVE FAMILY 4					
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVE		2-D	RL	ORVR
CERT	0.9	1.4	0.01	*	•	•		*	*	*		+	+	+	*	1
STD	2.0	2.5	0.05	*	*	*	•	•	*	*	+		*	*	+ +	 .

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 2014 day of August 2002.

Allen Lyons, Chief

Mobile Source Operations Division