

## GENERAL MOTORS CORPORATION

EXECUTIVE ORDER A-006-1104-2 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI YEA		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=light- MDV=medium-duty vehicle; L\ vehicle weight; ALVW=adjus	/W≃loaded	CATEGOR' vehicle; T	EMISSION STANDA Y (LEV=low emiss 'LEV= transitional LEV; LEV; SULEV=super ULI	ion EVAPORATIVE USEFUL LIFE	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)					
200	3 3	3GMXT06.0187			MDV: 5,751-8,500 pounds	s ALVW		LEV	120K / 120K (EVAF1, 2), 150K (EVAF3)	Gasoline (Indolene)					
No.		ORATIVE LY (EVAF)		No	SPECIAL FI EMISSION CONTRO			* = not applicable	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S						
1	3GMX	MXE0111911			SFI,	2TWC, 2HC	2S(2), OBD (F	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AiR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board							
2	3GMX	3GMXE0111920				4									
3	3GMX	MXE0111952				*									
4		*		4		*		diagnostic prefix 2=parallel (2) suffix=series							
EVAI No.		ECS ENGINE No. SIZE (L)			VEHICLE . MAKES & MODELS			CLES SUBJECT TO SFTP DARDS ARE UNDERLINED ABBREVIATIONS:							
1	1	1	6.0		Cadillac Escalade AW	C K1500 Yukon AWD, K1500 Sierra Denali AWD									
2	1	1	6.0		Cad	Cadillac Escalade EXT AWD, Escalade ESV AWD; GMC K1500 Yukon XL AWD									
3	1	1 6.0				Cadillac Escalade AWD, Escalade EXT AWD, Escalade ESV AWD; Chevrolet K1500 Silverado SS AWD; GMC K1500 Yukon AWD, K1500 Yukon XL AWD, K1500 Sierra Denall AWD									
	,	* *						*							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF AVERAGE [g/mi] CH4 RAF =				NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of introgen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diumal+hot-soak RL [g/mi]=running loss ORVR [g/gatlon dispensed]=on-board refueling vapor recovery g=gram												
CER	T	STD	NMOG NMHC		NMHC	mg≃milli	gram mi:	:clg/////j−/c =mile K=	1000 miles	F=de	grees F	anspenseu) Arenheit		erueling vap piemental fe			
*		*	CER		CERT [g/mi]	[g/mi]	CC	[g/mi]	/mi] NO:			HCHO [mg/		PM [c			Ox [g/mi]
			[g/m	i]		(g/m)	CERT	STD	CER	T S1	D C	CERT	STD	CERT	STD	CERT	STD
		@ 50K	0.07	3	*	0.195	2.8	5.0	0.1	0.	6	1	22	*	*	0.1	1.2
		@ UL	0.08	8	*	0.280	5.4	7.3	0.3	0.	9	1	32	*	*	0.3	1.8
1.4	@ 50	°F & 4K	*		*	*	*	*	*	,		*	*	*	*	*	*
CO [ @ 20		SFTP 1	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)						[g/mi] posite)						HC+NOx ni] [SC03]		[g/mi] 003]
50K		SFTP 2 = @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	STD	CE	RT ST	CER	r STD	CERT	STD		
CERT	10.4			i	SFTP 1	*	*	*	*	*	*	•	*	*	*	*	+
STD	12.5				SFTP 2	*	*	*	*	*	*	•	*	*	*	*	•
@ UL	EVAPORATIVE FAMILY 1					EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
	3-D	2-[	)	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV	R 3-D	2-D	RL	ORVR
CERT	1.3	1.4	4 C	0.00	*	1.6	2.2	0.00	*	0.60	0.60	0.0	*	*	*	*	
STD	2.0	2.5	5 0	0.05	•	2.5	3.0	0.05	*	0.90	1.15	0.0	5 *	•	*	*	*

**BE IT FURTHER RESOLVED:** That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-006-1104-1 dated October 3, 2002.

Executed at El Monte, California on this \_\_\_\_\_\_\_ day of October 2002.

Allen Lyons, Chief

Mobile Source Operations Division