

GENERAL MOTORS CORPORATION

EXECUTIVE ORDER A-006-1112
New Passenger Cars, Light-Duty Trucks
and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP		N	VEHICLE TYPE 'C=passenger car; LDT=light-duty tri IDV=medium-duty vehicle; LVW=loa vehicle weight; ALVW=adjusted LVI	uck; CATEGOR ded vehicle;	EMISSION STAND, Y (LEV=low emis TLEV= transitional LEV LEV; SULEV=super UL	sion EVAPORATIV						
200	3	3GMXT06.0194		4	MDV: 5,751-8,500 pounds ALV	~	LEV	120K / 120K	Gasoline (Indolene)					
No.		VAPORATIVE AMILY (EVAF)		No. SPECIAL FEATURES EMISSION CONTROL SYSTEM		RES & STEMS (ECS)	* = not applicable	OC/TWC=oxidizing/3-	way cat. ADSTWC=adsorbing TWC					
1	3GM)	MXE0133917				2HO2S(2), OBD (WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust							
2		*				*	gas recirculation AIR AIR MFI/SFI= multi	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI						
3		*				*	TBI= throttle body injection TC/SC=turbo /super charger							
4		*		4		*	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series							
EVA		ECS	ENGINE		VEHICLE	VEHICLES SUB.	ARRESTATIONS							
No.	l N	10.	SIZE (L)	MAKES & MODELS	STANDARDS AR	ABBREVIATIONS: *							
1		1	6.0				Hummer H2 4WD	/D						
*	* *						* ************************************							
*		*	*		*									
*		* *					*							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET AVERAGE [g/mi]		NMOG @ RAF=1.0 CH4 RAF = *		NMOG or	nitrogen	HUHU=10	rmaldehvde	e PM≕par	rticulate n	natter	RAF=reactiv	rbon CO=ca	nt factor	2/3 D [a/toct	1-2/2 days	
CER	CERT STD		NMOG	NMHC	NMHC STD	mg=millig	ot-soak K	∟ լց/mıj≖ru	nning loss 1000 miles	ORVR	g/gallor	n dispensed] ahrenheit	on-board re	fueling vap	or recovery	g=gram	
		* @ 50K	CERT [g/mi]	CERT [g/mi]	[g/mi]		[g/mi]				HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi		
						CERT	STD	CERI	ST	D C	ERT	STD	CERT	STD	CERT	STD	
	图 有点点		0.114	*	0.195	4.1	5.0	0.4	0.6	3	2	22	*	*	0.5	1.2	
4		@ UL	0.114	*	0.280	4.1	7.3	0.4	0.9	•	2	32	*	•	0.5	1.8	
	@ 50°	F & 4K	0.149	*	0.390	3.7	5.0	0.1	0.6	3	1	44	*	*	*	*	
	CO [g/mi] @ 20°F & 50K		LEV) or 50K (Tier 1, TLEV			NMHC+NOx [g/mi] CO [g/n (composite) (compos			NMHC+NOx [g/mi] [US06]				IC+NOx	CO [g/mi] [SC03]			
50			SFTP 2 = @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	STD	CE	RT STI	CERT	STD	CERT	STD	
CERT	. *	12.0		SFTP 1	*	*	*	*	*	*	١,	* *	•		*	*	
STD	*			SFTP 2	*	*	•	*	*	*	 	* *	•	•	*	*	
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EV				EVA	EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVI		2-D	RL	ORVR	
CERT	1.6	1.7	0.00	*	*	*	*	*	*	*	*	•	*	*	*	*	
STD	3,0	3.5	0.05	*	*	*	*	*	*	*	*	*	•	*	*	+	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 26th day of February 2002.

Allen Lyons, Chief

New Vehicle/Engine Programs Branch