

BAYERISCHE MOTOREN WERKE AG

EXECUTIVE ORDER A-008-0158
New Passenger Cars, Light-Duty Trucks
and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD: YEA		TEST GROUP			ME	VEHICLE TYPE E-passenger car; LDT=light-duty truck; DV=medlum-duty vehicle; LVW=loaded ehicle weight; ALVW=adjusted LVW)	CATEGOR vehicle: 1	EMISSION STANDAY (LEV=low emis LEV= transitional LEV LEV; SULEV=super UL	sion :	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)				
200	3	3BMXT04.4E53			M	DV: 3,751 - 5,750 pounds ALVW		LEV		120K / 120K	Gasoline				
No.		PORA ILY (E	No) .	SPECIAL FEATURES EMISSION CONTROL SYSTEM		* = not applicable	OC W	OC/TWC=oxidizing/3-way cat. ADSTWC=adsort						
1	3BM)	BMXR0160E39				2TWC, 2HO2S(2), \$		A	WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI						
2		*						ga All							
3		*				*		TE	Bl= throttle body injection	on TC/SC=turbo /super charger					
4		*				*		CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series							
EVAF No.		CS No.	ENGIN SIZE (L					ECT TO SFTP E UNDERLINED	ABB	REVIATIONS:					
1		1 4.4				BMW: X5, X5 Sport									
*		*	*					*							
*		*	*					*							
*		*	*					*	-						

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]			NMOG @ RAF = 0.94 CH4 RAF = *		NMOG or	or nitrogen	HCHU=	नormaider	ivde PM ≕	D articulate	matter	n-CH4 hydro RAF=read	tivity adius	tment factor	2/3 D (a/to	e+1=2/3 disv
CER	CERT STD		NMOG	NMHC CERT [g/mi]	NMHC STD [g/mi]	mg=milligr	t-soak K	∟ լg/m+j=rι	inni ng loss =1000 mile:	ORVR [g/	gailon	dispensed]	=on -board r	efueling vap plemental fe	or recovery	g=gram
*			CERT				g/mi]		Ox [g/mi]			mg/mi]	PM [Hwy NO	
			faunil	[8,111]		CERT	STD	OER	T ST	D CE	RT	STD	CERT	STD	CERT	STD
4 6 9	0	9 50K	0.084	* .	0.160	1.6	4.4	0.2	0.4	4 2	2	18	*	*	0.01	0.8
		@ UL	0.102	*	0.230	1.8	6.4	0.2	0.0	3 3	3	27	*	*	0.01	1.2
	@ 50°F	& 4K	0.157	*	0.320	1.9	4.4	0.1	0.4	1 2	2	36	*	*	*	*
CO [@ 20	°F&	LE'	= @ 4K (SULI V) or 50K (Ti	er 1, TLEV)	NMHC+NOx [g/mi] (composite)		CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]			O [g/mi] [US06]		HC+NOx ii] [SC03]		[g/mi] 203]
50	K	SFTP 2 = @ UL (Tie		1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CE	RT STE	CER	T STD	CERT	STD
CERT	4.7		拉表 12 维	SFTP 1	*	*	-		0.06	0.40	3.	2 10.5	0.05	0.31	0.2	3.5
STD	12.5	400	18.45	SFTP 2			1	*		*	*	*	*	*	. *	*
@ UL.			TIVE FAM		EVAPORATIVE FAMILY 2 EVAPORATIVE FAMIL							MILY 3	EVAPORATIVE FAMILY 4			
	3-D	2-D		ORVR	3 -D	2-D	RL	ORVR	3-D	2-D	RL	ORVE	₹ 3-D	2-D	RL	ORVR
CERT	1.6	1.9	0.02	0.04	* "		•	*	*	*	*	*	*	*	*	*
STD	2.0	2.5	0.05	0.20	*	X	*	*	*	*	*	*	*	*	*	*

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 23 4D day of September 2002.

Allen Lyons, Chief

Mobile Source Operations Division