

## DAIMLERCHRYSLER AG

Frele

EXECUTIVE ORDER A-003-0246 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| MOD<br>YEA  | R   | TEST GROUP                |                       |   | MD  | VEHICLE TYPE<br>=passenger car; LDT=light-duty truck;<br>IV=medlum-duty vehicle; LVW=loaded<br>ehicle weight; ALVW=adjusted LVW) | EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV) |                             |   | EXHAUST /<br>EVAPORATIVE<br>USEFUL LIFE<br>(UL) (miles)  | FUEL TYPE<br>(CNG/LNG=compressed/<br>liquefied natural gas;<br>LPG=liquefied petroleum gas) |  |  |  |  |
|-------------|-----|---------------------------|-----------------------|---|-----|--|---|-----------------------------|---|--|---|--|--|--|--|
| 200         | •   | 3MBXV05.5LBI              |                       |   |     | PC   | LEV   |                             |   | 100K / 100K  | Gasoline  |  |  |  |  |
| No.         | FAM | ILY (E                    | PORATIVE<br>LY (EVAF) |   |     | SPECIAL FEATURES<br>EMISSION CONTROL SYSTE   | &<br>MS (ECS)   | * = not applicable          | OC  | OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TO WU= warm-up cat. O2S/HO2S=oxygen sensor/heated C |   |  |  |  |  |
| 1           | 3MB | XR016                     | 88LNZ                 | 1 | - } | SFI, 2WUTWC, 2TWC, 2HO2  |   | □ MC                        | O/⊓Aro≃air-tuei ratio s   | iansor/heated AFS ECD-cubered  |   |  |  |  |  |
| 2           |     | *                         |                       |   | : 1 | *  |   | ga<br>Ali                   | S recirculation AIR/PAI   | R=secondary air injection/pulsed   |   |  |  |  |  |
| 3           |     | *                         |                       |   |     | *  |   | −Штв                        | II= INΓΩΠΙΑ ΝΛΑΥ INIACTIA   | t fuel injection/sequential MFI<br>on TC/SC=turbo /super charger                                 |   |  |  |  |  |
| 4           |     | *                         |                       |   |     |  |   |                             | CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series |  |   |  |  |  |  |
| EVAF<br>No. |     | CS ENGINE<br>No. SIZE (L) |                       |   |     | VEHICLE VEI<br>MAKES & MODELS STA  | HICLES SUBJ   | ECT TO SFTP<br>E UNDERLINED | - 13  | REVIATIONS: *  |   |  |  |  |  |
| 1           |     | 1 5.5                     |                       |   |     | MERCEDES-BENZ SL55 AMG KOMPRESSOR  |   |                             |   |  |   |  |  |  |  |
| *           |     | * *                       |                       | T |     | *  |   |                             |   |  |   |  |  |  |  |
| *           |     | *                         | *                     |   |     |  |   | *                           |   |  |   |  |  |  |  |
| *           |     | *                         | *                     |   |     |  |   | *                           |   |  |   |  |  |  |  |

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bidual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

| NM<br>AVE | NMOG FLEET<br>AVERAGE [g/mi] |                              | NMOG @ RAF=0.94<br>CH4 RAF = * |                | NMOG o               |                     |                             |           |                           |        |                         |         |                           | arbon mono                                 |                     |        |
|-----------|------------------------------|------------------------------|--------------------------------|----------------|----------------------|---------------------|-----------------------------|-----------|---------------------------|--------|-------------------------|---------|---------------------------|--|---------------------|--------|
| CER       |                              |                              | NMOG<br>CERT                   | NMHC           | NMHC<br>STD          | mg=milligr          | am mi≃                      | ~ [8,]rui | nning loss                | OKANIE | /gallon di<br>rees Fahi | spensed | on-board r                | ent factor<br>efueling vap<br>plemental fe | or recovery         | a≖aram |
| 0.05      | ВО                           | .062                         | [g/mi]                         | CERT<br>[g/mi] | [g/mi]               | CERT CO             | g/mi]                       |           | x [g/mi]                  | Н      | CHO [m                  | g/mi]   | PM [g                     | g/mi]                                      | Hwy NO              |        |
|           |                              | 0.5016                       |                                |                | <del></del>          | CERT                | STD                         | CERT      | ST                        | D CE   | RT                      | STD     | CERT                      | STD  | CERT                | STD    |
|           |                              | @ 50K                        | 0.028                          | *              | 0.075                | 1.0                 | 3.4                         | 0.04      | 0.2                       | 2 0    | .4                      | 15      | *                         | *  | 0.00                | 0.3    |
| 1         |                              | @ UL                         | 0.041                          | *              | 0.090                | 1.4                 | 4.2                         | 0.04      | 0.5                       | 3      | 1                       | 18      | *                         | *  | 0.00                | 0.4    |
|           | @ 50°l                       | F & 4K                       | 0.039                          | *              | 0.150                | 0.4                 | 3.4                         | 0.03      | 0.2                       | 2 0    | .4                      | 30      | *                         | *  | *                   | *      |
| @ 20      | CO [g/mi]<br>@ 20°F &<br>50K |                              | LEV) or 50K (Tier 1, TLEV)     |                |                      | Ox [g/mi]<br>osite) | i] CO [g/mi]<br>(composite) |           | NMHC+NOx<br>[g/mi] [US06] |        | CO [g/mi]<br>[US06]     |         | NMHC+NOx<br>[g/mi] [SC03] |  | CO [g/mi]<br>[SC03] |        |
| -         | ^                            | SFTP 2 = @ UL (Tier 1, TLEV) |                                |                | CERT                 | STD                 | CERT                        | STD       | CERT                      | STD    | CERT                    | STD     |                           |  | CERT                | STD    |
| CERT      | 1.6                          |                              |                                | SFTP 1         | *                    | *                   |                             | *         | *                         | *      | *                       | *       | *                         | *  | #                   | 310    |
| STD       | 10.0                         |                              |                                | SFTP 2         | *                    |                     |                             | *.        | •                         | *      | *                       | *       | *                         | -  |                     | -      |
| @ UL      | EVAPORATIVE FAMILY 1         |                              |                                |                | EVAPORATIVE FAMILY 2 |                     |                             |           | EVAPORATIVE FAMILY 3      |        |                         |         | 1 521                     | /APORATI                                   | \/F F A A & !!      | V 4    |
|           | 3-D                          | 2-D                          | RL                             | ORVR           | 3-D                  | 2-0                 |                             | ORVR      | 3-D                       | 2-D    |                         |         |                           | 7  |                     |        |
| CERT      | 1.2                          | 1.6                          | 0.00                           | 0.01           |                      |                     |                             | OKAK.     | 3-0                       |        | RL                      | ORVR    | 3-D                       | 2-D  | RL                  | ORVR   |
| STD       | 2.0                          | 2.5                          | 0.05                           |                |                      |                     |                             |           | -                         | *      | *                       | *       | *                         | *  | *                   | *      |
| <u> </u>  | 2.0                          | 2.5                          | 0.05                           | 0.20           |                      |                     |                             | *         | *                         | *      | *                       | *       | *                         | *  | *                   | *      |

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of July 2002.

Allen Lyons, Chief

Mobile Source Operations Division