

GENERAL MOTORS CORPORATION

EXECUTIVE ORDER A-006-1079 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR TE			TEST GROUP			VEHICLE TYPE C=passenger car; LDT=ilght-duty truck; DV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
2003 3GM			XV02.20	26		PC	LEV			100K / 100K	Gasoline			
No.		EVAPORATIVE FAMILY (EVAF)			No.	SPECIAL FEATURES EMISSION CONTROL SYSTE		* = not applicable	OC WI	C/TWC=oxidizing/3-way	cat. ADSTWC=adsorbing TWC O2S=oxygen sensor/heated O2S			
1	3GN	3GMXR0124919			1	SFI, TWC, HO	2S(2), OBD (P)	AF	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board					
2		*			2	1		– Iga Ali						
3		*			3	,	•	TE						
4		*			4	1		dia	diagnostic prefix 2=parallel (2) suffix=series					
EVAI No.	ECS ENGINE						ECT TO SFTP E UNDERLINED	ABBI	ABBREVIATIONS: *					
1	1 2.2		T	Saturn Ion										
*		*	*			*								
*	* *					*								
*		* *												

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	OG FI RAGE	LEET [g/mi]	NMOG @ CH4 R	RAF=0.94 AF = *	NMOG or	nitrogen	HCHO=for	maldehyde	PM≃part	iculate mat	ter R	4 hydrocarb AF=reactivit	v adiustme	nt factor	2/3 D fa/test	=2/3 day
CER	CERT STD		NMOG	NMHC	NMHC	mg=millig	x-soak Ki ram mi≃	- [g/mɪ]=run mile K=1	ning loss	ORVR [g/g F≂dear	ialion d ees Fai	lispensed]=d renheit			or recovery deral test pr	
0.060	0	0.062	CERT	CERT [g/mi]	[g/mi]		[g/mi]		x [g/mi]	HC	HO [m		PM [g		Hwy NO	
			[g/mi]			CERT	STD	CERT	STE	CEF	₹T	STD	CERT	STD	CERT	STD
	@ 50K		0.037	*	0.075	0.9	3.4	0.2	0.2	0.9	5	15	*	*	0.1	0.3
	@ U		0.037	*	0.090	0.9	4.2	0.2	0,3	.3 0.5	5	18	*	*	0.1	0.4
	@ 50	°F & 4K	0.060	*	0.150	1.3	3.4	0.03	0.2	0.4	1	30	*	*	*	*
	@ 20°F &								[g/mi] NMHC+N nposite) [g/mi] [US				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
50						STD	CERT	STD	CERT	STD	CER	T STD	CERT	STD	CERT	STD
CERT	4.4			SFTP 1	*	*	*	*	0.05	0.14	3.4	8.0	0.04	0.20	0.8	2.7
STD	10.0]		SFTP 2	*	*	*	*	*	*	*	*	*	*	*	*
@ UL		EVAPOR	ATIVE FAN	IILY 1	EVAPORATIVE FAMILY 2 EVA					PORATIVI	FAN	IILY 3	EVAPORATIVE FAMILY 4			
U	3-D	2-[RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR
CERT	0.6	0.7	7 0.00	0.02	*	*	*	*	*	*	*	*	*	*	*	*
STD	2.0	2.	0.05	0.20	*	*	*	*	*	•	*	•	•	•	*	*

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 2014 day of May 2002.

Aller Lyons, Chief

New Vehicle/Engine Programs Branch