

## **GENERAL MOTORS CORPORATION**

EXECUTIVE ORDER A-006-1082
New Passenger Cars, Light-Duty Trucks
and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| MOD<br>YEA       |              | TEST GROUP                 |                  | Р | VEHICLE TYPE (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW) |                                     |        | EXHAUST EMISSION STANDARI CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV] |       |   | EXHAUST /<br>EVAPORATIVE<br>USEFUL LIFE<br>(UL) (miles)  | FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas) |  |  |  |
|------------------|--------------|----------------------------|------------------|---|--|-------------------------------------|--------|---|-------|---|--|--|--|--|--|
| 2003 3GMXV02.300 |              |                            | )1               |   | PC   |                                     | LEV    |   |       | 100K / 100K   | Gasoline (Indolene)  |  |  |  |  |
| No.              |              | VAPORATIVE<br>AMILY (EVAF) |                  |   | lo.  | SPECIAL FEATU<br>EMISSION CONTROL S | JRES & | & *= not applicable   |       |   | OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC   |  |  |  |  |
| 1                | 3GM          | 3GMXR0124919               |                  |   | 1  | SFI, WUTWC, TWC,                    |        |   | Al    | WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S<br>AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust |  |  |  |  |  |
| 2                | 3GMXR0133910 |                            |                  |   | 2  | SFI, TWC, HO2S(2), TC, CAC, OBD (F) |        |   |       |   | gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series |  |  |  |  |
| 3                | *            |                            |                  | П | 3  |                                     |        |   |       |   |  |  |  |  |  |
| 4                |              | *                          |                  |   | 4  |                                     |        |   |       |   |  |  |  |  |  |
| EVAI<br>No.      |              | ECS<br>No.                 | ENGIN<br>SIZE (I |   |  |                                     |        | IICLES SUBJECT TO SFTP  |       |   | ABBREVIATIONS: *   |  |  |  |  |
| 1                |              | 1                          | 2.0              |   |  |                                     |        | SAAB 9-3  | artia | artial OBD)   |  |  |  |  |  |
| 2                |              | 2                          | 2.0              |   |  | SAAB 9-3 SPORT SEDAN (Full OBD)     |        |   |       |   |  |  |  |  |  |
| 1.               |              | 1                          | 2.3              |   | SAAB 9-5, 9-5 WAGON (Full OBD)   |                                     |        |   |       |   |  |  |  |  |  |
| *                |              | *                          | *                |   | •  |                                     |        |   |       |   |  |  |  |  |  |

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

|      | NMOG FLEET NMOG @ RAF=1.<br>AVERAGE [g/mi] CH4 RAF = * |         |   |                        | NMOG or               | Introgen            | HCHU=TO                  | rmaidenvde    | PM≖bar                    | ticulate m           | atter   | RAFereactiv             | rbon CO=c   | ant factor                   | 2/2 D In/toes       | 1-2/2 da   |  |
|------|--|---------|---|------------------------|-----------------------|---------------------|--------------------------|---------------|---------------------------|----------------------|---------|-------------------------|-------------|------------------------------|---------------------|------------|--|
| CER  | 0.060 0.062  |         | NMOG  | NMHC<br>CERT<br>[g/mi] | NMHC<br>STD<br>[g/mi] | mg=millig           | ot-soak k                | r [g/mı]≃ırıı | nning loss<br>000 miles   | ORVR [g              | /gallon | dispensed]<br>ahrenheit | ≖on-board r | efueling vap<br>plemental fe | or recovery         | g≖gram     |  |
| 0.06 |  |         | CERT<br>[g/mi]  |                        |                       |                     | [g/mi]                   | NC            | x [g/mi]                  | H                    | нсно    | [mg/mi]                 | PM [9       |                              | Hwy NO              |            |  |
|      |  | ,       |   | [A,ıııı]               | -                     | CERT                | STD                      | CERT          | ST                        | ) CE                 | RT      | STD                     | CERT        | STD                          | CERT                | STD        |  |
|      | @ 50K  |         | 0.058   | *                      | 0.075                 | 1.2                 | 3.4                      | 0.1           | 0.2                       | 2 0                  | .2      | 15                      | *           | *                            | 0.03<br>0.1         | 0.3<br>0.4 |  |
|      |  | @ UL.   | 0.067   | *                      | 0.090                 | 1.4                 | 4.2                      | 0.2           | 0.3                       | 0.3 0.3              |         | 18                      | *           |                              |                     |            |  |
| i A  | @ 50   | °F & 4K | 0.098   | *                      | 0.150                 | 1.4                 | 3.4                      | 0.01          | 0.2                       | . 0                  | .3      | 30                      | *           | *                            | *                   | *          |  |
|      | @ 20°F &   |         | SFTP 1 = @ 4K (SULEV, ULEV,<br>LEV) or 50K (Tier 1, TLEV)<br>SFTP 2 = @ UL (Tier 1, TLEV) |                        |                       | Ox [g/mi]<br>osite) | CO [g/mi]<br>(composite) |               | NMHC+NOx<br>[g/mi] [US06] |                      |         | CO [g/mi]<br>[US06]     |             | HC+NOx                       | CO [g/mi]<br>[SC03] |            |  |
| 50   |  |         |   |                        |                       | STD                 | CERT                     | STD           | CERT                      | STD                  | CE      | RT STI                  |             |                              | CERT                | STD        |  |
| CERT | 4.2  |         | 10.00   | SFTP 1                 | *                     | *                   | •                        | *             | 0.06                      | 0.14                 | 0.      | 5 8.0                   | 0.02        | 0.20                         | 0.1                 | 2.7        |  |
| STD  | 10.0   |         |   | SFTP 2                 | *                     | *                   |                          | *             | *                         | *                    | ٠,      |                         | •           | *                            | *                   | *          |  |
| @ UL | Е  | VAPOR.  | ATIVE FAN   | IILY 1                 | EVAPORATIVE FAMILY 2  |                     |                          |               |                           | EVAPORATIVE FAMILY 3 |         |                         |             | EVAPORATIVE FAMILY 4         |                     |            |  |
|      | 3-D  | 2-[     | RL  | ORVR                   | 3-D                   | 2-D                 | RL                       | ORVR          | 3-D                       | 2-D                  | RL      | ORVI                    |             | 2-D                          | RL                  | ORVR       |  |
| CERT | 1.5  | 1.8     | 0.00  | 0.08                   | 1.2                   | 1.2                 | 0.00                     | 0.09          | *                         | *                    |         | -                       | *           | •                            | *                   | *          |  |
| STD  | 2.0  | 2.5     | 0.05  | 0.20                   | 2.0                   | 2.5                 | 0.05                     | 0.20          | •                         | *                    |         | *                       | •           | +                            |                     | <b> </b> • |  |

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of August 2002

Allen Lyons, Chief

Mobile Source Operations Division