VOLKSWAGEN AG

EXECUTIVE ORDER A-007-0232 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL TEST			T GRO	UP	M	VEHICLE TYPE C=passenger car; LDT=light-duty truck; DV=medium-duty vehicle; LVW=loaded rehicle weight; ALVW=adjusted LVW)	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200		3VWXV04.0229				PC	LEV			100K / 100K	Gasoline				
No.	FAN	APORA MILY (E	EVAF)		No.	SPECIAL FEATURES EMISSION CONTROL SYSTE		* = not applicable	OC	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWU=warm-up cat. O2S/HO2S=oxygen sensor/heated					
1	3VW	VXR01	40234		1	2TWC, 2HO2S(2),	AIR, SFI, OBC	BAr.	>/HAF>=air∙tuel ratio s	ensor/heated AFS_FGD=evhaget					
2		*			2			- gas	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo/super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
3		*			3	*		ТВ							
4		*			4	*		HCA							
EVAF No.		CCS ENGINE VEHICLE VEHICLES SUBJECT TO SF No. SIZE (L) MAKES & MODELS STANDARDS ARE UNDERLIN				ECT TO SFTP	ABBREVIATIONS: *								
1		1 4.0			T	VOLKSWAGEN PASSAT W8 4MOTION SEDAN / WAGON									
*	* *					*									
*		*	*					*							
*	* *				T	*									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NM AVE	NMOG FLEET AVERAGE [g/mi] CERT STD			RAF=0.94 RAF = *	NMOG or							H4 hydroca RAF=reactiv					
CER			NMOG	NMHC	NMHC	mg=millig	N-SUAK N	r faunil∞i a	nning loss 1000 miles	UKVK	g/gallor	dispensed] ahrenheit	=on-board r	efueling vap elemental fe	or recovery	q=qram	
0.05	6 6	0.062	CERT [g/mi]	CERT [g/mi]	[g/mi]		[g/mi]		x [g/mi]	Н	ICHO	mg/mi]	PM [g		Hwy NO		
144	N CONTRACT CONTRACT		[a,]			CERT	STD	CERT	STI	D CI	ERT	STD	CERT	STD	CERT	STD	
		@ 50K	0.023	*	0.075	1.0	3.4	0.1	0.2	2	1	15	*	*	0.02	0.3	
	14	@ UL	0.028	*	0.090	1.1	4.2	0.1	0.3		1	18	*	*	0.02	0.4	
	@ 50	°F & 4K	0.043		0.150	1.2	3.4	0.1	0.2	:	1	30	*	•	*	*	
CO [@ 20	g/mi] °F &	Li	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			Ox [g/mi] osite)	CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]			
50	K	SFTP 2 = @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	STD	CE				CERT	STD		
CERT	1.9	1.23	2 a)(1.)	SFTP 1	*	*	*		0.03	0.14	1.	2 8.0			1.8	2.7	
STD	10.0		Maria di	SFTP 2	*	*	*	*	*		 		*	*	•	*	
@ UL			ATIVE FAI	VILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				E\	EVAPORATIVE FAMILY 4			
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVI		2-D	RL	ORVR	
CERT	1.2	1.3	0.000	0.03	•	•	*	*	*	*	*		* 3-5	*	NL	*	
STD	2.0	2.5	0.05	0.20	*	•	*		*	*		-	*	+	+	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of June 2002.

Allen Lyons, Chief

Mobile Source Operations Division