

## **BAYERISCHE MOTOREN WERKE AG**

EXECUTIVE ORDER A-008-0151 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP				VEHICLE TYPE C=passenger car; LDT=light-duty uck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	EXHAUST EN STANDARD CA (LEV=low emissic TLEV= transitio ULEV=ultra SULEV=super	TEGORY on vehicle; na! LEV; LEV;		CHAUST & ORVR / EVAPORATIVE UL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
2003		3BMXV03.0M5R			PC	ULEV		100K 100	/ 100K (EVAF 1 & 2) K / 150K (EVAF 3)	Gasoline					
No.		APOR <i>a</i> MLY (E		N	o.	SPECIAL FEATU EMISSION CONTROL S		* = not app		cable OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing					
1	3BM	3BMXR0136E46				2TWC, 2HO2	S(2), SFI, AIR, OBD	WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust							
2	3BM	3BMXR0160E39			2		*	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger							
3	3BM	3BMXR0128E85			3		*								
4		*			4		*	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series							
EVAF No.	1 1		ENGIN SIZE (			VEHICLE MAKES & MODELS	VEHICLES SUBJESTANDARDS ARE			BBREVIATIONS:					
1		1 3.0				BMW: 330I, 330Ci, 330Ci Convertible									
2		1	3.0												
3		1 3.0			BMW Z4 3.0i										
*		* *						*							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET AVERAGE [g/mi]			RAF = 0.94 RAF = *		CH4=methane NMOG=non-CH4 organic gases NMHC=non-CH4 hydrocarbons CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram											
CER	CERT STD		NMOG	NMHC	NMHC	diurnai+h mg=millig	ursuak k	և լց/ում=ւս	nning los 1000 mile	S URV	K (g/gallo	n dispensed] Fahrenheit	on-board re- SFTP=sup	fueling vap	or recovery	g=gram	
0.05	0.057 0.062		CERT CERT [g/mi]		[g/mi]		[g/mi]		Ox [g/mi	L	НСНО	[mg/mi]	PM [g		Hwy NO		
				[3,1,1,1]		CERT	STD	CER	r S	TD	CERT	STD	CERT	STD	CERT	STD	
		@ 50K	0.011	*	0.040	0.8	1.7	0.04	0	.2	0.2	8	*	*	0.01	0.3	
150		@ UL	0.012	*	0.055	0.9	2.1	0.05	0	.3	0.2	11	*	*	0.01	0.4	
	@ 50°	F & 4K	0.028	*	0.080	0.4	1.7	0.03	0	.2	0.1	16	*	*	*	*	
CO [ @ 20	°F&	L		ier 1, TLEV)	NMHC+NO (comp				NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]			
50	50K		= @ UL (Tie	r 1, TLEV)	CERT	STD	CERT	STD	CERT	ST	D CE	RT STI	CERT	STD	CERT	STD	
CERT	2.1	1.9	3147	SFTP 1	*	*	*	•	0.03	0.1	14 0	.3 8.0	0.04	0.20	0.5	2.7	
STD	10.0		48.42	SFTP 2	*	*	*	*	*	*		* *	*	*	*		
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				E	EVAPORATIVE FAMILY 4			
	3-D	2-[		ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RI	ORVI		2-D	RL	ORVR	
CERT	0.7	1.5			1.7	1.8	0.03	0.04	0.45	0.27	7 0.0	1 0.06	*	*	*	*	
STD	2.0	2.5	0.05	0.20	2.0	2.5	0.05	0.20	0.50	0.65	5 0.0	5 0.20	*	*	*	•	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 23 kb day of September 2002.

Allen Lyons, Chief

Mobile Source Operations Division