

FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1099 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD		TEST GROUP			VEHICLE TYPE PC=passenger car; LDT=light-duty truck MDV=medium-duty vehicle; LVW=loadec vehicle weight; ALVW=adjusted LVW)	CATEGOR	EMISSION STANDA Y (LEV=low emis TLEV= transitional LEV LEV; SULEV=super UL	sion EVAPORATIVE USEFUL LIFE	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
2003 3FMXT02.01F				5	LDT: 0-3,750 pounds LVW		LEV	100K / 100K	Gasoline (Tier 2 Unleaded)				
No.		APORATIVE IILY (EVAF)		No	SPECIAL FEATURE EMISSION CONTROL SYST	S & EMS (ECS)	* = not applicable	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWG WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2					
1	3FM	3FMXR0115BBE			TWC, HO2S(2),	EGR, SFI, OBD	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo/super_charger						
2		*				*							
3		*				*							
4		*				*	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
EVAI No.						JECT TO SFTP	ABBREVIATIONS:						
1		1	2.0			WD	·						
*		*	*		*								
*		*	*										
*		*	*	*									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET NMOG @ RAF= * AVERAGE [g/mi] CH4 RAF = *			NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/ml]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram											
CER	CERT STD		NMOG	NMHC	NMHC STD	mg=millig	ot-soak Ki	և լց/mij=run	ining loss 000 miles	ORVR [g	g/gallon	dispensed] threnheit	=on-board r	efueling var	or recovery derail test pr	g=gram
0.05	0.053 0.062		CERT [g/mi]	CERT [g/mi]	[g/mi]	CO [g/mi]		NOx [g/mi]		Н	HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]	
THE WAY			[g/mj			CERT	STD	CERT	STE	CI	ERT	STD	CERT	STD	CERT	STD
		@ 50K	0.038	*	0.075	0.9	3.4	0.1	0.2		1	15	*	*	0.1	0.3
1	- 41	@ UL	0.048	*	0.090	1.1	4.2	0.1	0.3		1	.18	*	*	0.1	0.4
4	@ 50	°F & 4K	*	*	*	*	*	*	*		*	*	*	*	*	*
CO [@ 20	°F&	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			NMHC+NOx [g/mi] CO [g/ (composite) (compo							O [g/mi] [US06]		HC+NOx ii] [SC03]		[g/mi] 203]
50K		SFTP 2 = @ UL (Tier 1,		er 1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CEI	RT STI	CER	r STD	CERT	STD
CERT	1.5		10年15月	SFTP 1	*	*	*	*	0.08	0.14	2.1	8.0	0.05	0.20	1.3	2.7
STD	10.0			SFTP 2	*	*	*	•	*	*	*	*	*	*	*	*
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EVAPOR				PORATI	RATIVE FAMILY 3			EVAPORATIVE FAMILY 4			
	3-D	2-[RL	ORVR	3-D	2-D	RL.	ORVR	3-D	2-D	RL	ORVI	R 3-D	2-D	RL.	ORVR
CERT	1.0	0.9	0.01	0.18	*	*	*	*	*	*	*	*		*	*	*
STD	2.0	2.5	0.05	0.20	*	*	*	*	*	•	*	*	*	*	*	*

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____ day of July 2002

Allen Lyons, Chief

Mobile Source Operations Division