



## FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1105 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

	MODEL TEST GROUP			Р	M	VEHICLE TYPE C=passenger car; LDT=light-duty truck; DV=medium-duty vehicle; LVW=loaded rehicle weight; ALVW=adjusted LVW)	CATEGOR' vehicle: 1	EMISSION STANDA Y (LEV=low emiss rLEV= transitional LEV; LEV; SULEV=super ULI	ion EVAPORATIVE USEFUL LIFE	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
200	2003 3FMXT03.02F6					LDT: 3,751-5,750 pounds LVW		LEV	100K / 100K	Flexible Fuel: Ethanol (E85) /Gasoline (Indolene)			
No.	FAM	IILY (E	(EVAF)		EVAF)		No.	SPECIAL FEATURES EMISSION CONTROL SYSTE	& MS (ECS)	* = not applicable	OC/TWC=oxidizing/3-way	cat. ADSTWC=adsorbing TWC HO2S=oxygen sensor/heated O2S	
1	3FM	IXR0155FBE			1 .	2TWC, TWC, TWC(2), 2H	02S, HO2S, S	AFS/HAFS=air-fuel ratio	sensor/heated AFS_EGR=exhaust				
2		*			2	•		gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series					
3		*			3	7							
4		*			4								
EVAI No.		ECS ENGINE No. SIZE (L)			VEHICLE VE MAKES & MODELS STA	HICLES SUBJ NDARDS AR	ECT TO SFTP E UNDERLINED	ABBREVIATIONS:					
1	1 3.0		T	Ford Ranger Pickup 2WD FFV; Mazda B3000 2WD FFV									
*		*	*										
*		*	*		1								
*	* *				T -	•							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]		NMOG @ RAF=0.854 (1.00) CH4 RAF = *			NMOG or NMHC	diurnal+ho	HCHO≕for ot-soak R	maldenyde L [g/mi]=runi	PM≖pari ning loss	ticulate ma ORVR [g	atter /gallor	RAF≃reacti dispensed	vity adjustn ]=on-board	carbon mono	2/3 D lattact	1-7/2 44	
CERT	STD			STD	diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g-gram mg=milligram mi=mile K=1000 miles F=degrees Fahrenheit SFTP=supplemental federal test procedure												
0.094	0.093	CERT		CERT	[g/mi]		[g/mi]		Ox [g/mi]   I		HCHO [mg/mi]		PM [	[g/mi]	Hwy NOx [g/mi]		
		[g/mi]		[g/mi]		CERT	STD	CERT	STE	CE	RT	STD	CERT	STD	CERT	STD	
	@ 50K	0.085		*	0.100	0.6	4.4	0.02	0.4		2	18			0.03	0.5	
		(0.017			(0.160)	(0.5)	(4.4)	(0.04)	(0.4		1)	(18)			(0.05)	(0.5)	
The second	@ UL	0.103		*	0.130	0.9	5.5	0.03	0.5	. 1		23	*		0.04	0.7	
		(0.032			(0.200)	(0.7)	(5.5)	(0.1)	(0.5	) (	1)	(23)			(0.1)	(0.7)	
@ 5	0°F & 4K	*		*	*	*	*		*	- 1	*	*	*	* (	*	*	
CO [ @ 20	°F&	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			NMHC+NC (compo				NMHC+NOx [g/mi] [US06]				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50	K	SFTP 2 = @	UL (Tier 1	, TLEV)	CERT	STD	CERT	STD	CERT	STD	CE	RT ST			CERT	STD	
CERT	1.8 (2.7)			SFTP 1	*	*	*	*	(0.09)	(0.25)	(2.	.0) (10.	5) (0.03	3) (0.27)	(0.1)	(3.5)	
STD	12.5 (12.5)			SFTP 2	*	*	*	*	*	*	•	• •	*	•	*	•	
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EVAPO					PORATIV	ORATIVE FAMILY 3			EVAPORATIVE FAMILY 4			
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV		2-D	RL	ORVR	
CERT	1.3	1.3	0.01	0.02	*	*	*	*	*	*	*	*	*	*	*	*	
STD	2.0	2.5	0.05	0.20	*	*	*	*	•	*		*	*		*		

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 12 th day of July 2002.

Allen Lyons, Chief

Rese Cratis

Mobile Source Operations Division