

FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1107 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL TEST GRO					MDV veł	VEHICLE TYPE passenger car; LDT=light-duty truck; =medium-duty vehicle; LVW=loaded nlcle weight; ALVW=adjusted LVW) DT: 3,751-5,750 pounds LVW	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV) 1) USEPA Bin 8 2) Counted as ARB LEV I ULEV			EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles) 100K / 100K	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas) Gasoline (Tier 2 Unleaded)				
No.		VAPORATIVE AMILY (EVAF)			١.	SPECIAL FEATURES EMISSION CONTROL SYSTE	& MS (ECS)	* = not applicable	OC	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC					
1	3FM	SFMXR0230BBE			\top	2TWC, 2HO2S(2), I		AF	WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/yeulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body Injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
2		*				*	· · · · · · · · · · · · · · · · · · ·	gas							
3		*				*		−Птв							
4		* 5			_	*	· · · · · · · · · · · · · · · · · · ·	ICA							
EVAI No.					VEHICLE VEI MAKES & MODELS STA	HICLES SUB. NDARDS AR	ECT TO SFTP	T TO SFTP APPREMATIONS							
1		1 3.8				Ford Windstar FWD Cargo Van; Ford Windstar FWD Wagon									
*		*	*												
*		*	*			*									
*	* * *														

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	OG FL RAGE		NMOG @ RAF= * CH4 RAF = *		NMOG or NMHC NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NMOG or nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor remainded.									2/2 D I /44	1-0/0		
CER	CERT STD		NMOG	NMHC	NMHC STD	diurnal+ho mg=milligi	n-soak K	r [8/mi]=tui	nning loss 000 miles	UKVK	[g/galloi	n dispensed ahrenheit]=on-board r	efueling vap plemental fe	or recovery	g≂gram	
0.09	4	.093 CERT CERT		[g/mi]		CO [g/mi]		x [g/mi]		нсно	[mg/mi]	PM (Hwy NO			
. = 3653466	dr., sinii Jones de Col		[8,,,,,]	[9,]		CERT	STD	CERT	STI	2 0	CERT	STD	CERT	STD	CERT	STD	
		@ 50K 0.040		*	0.100	0.6	3.4	0.05	0.1	0.4		15	*	*	0.04	0.19	
300		@ UL	0.062	*	0.125	0.9	4.2	0.05	0.2	0	1	18	*	*	0.04	0.27	
	@ 50	°F & 4K	*	*	*	*	*	*	*		*	*	*	*	*	*	
	g/mi] °F &				NMHC+NO (comp		ni] CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50	K				CERT	STD	CERT	STD	CERT	STD	CE	RT ST			CERT	STD	
CERT	1.3		SI	FTP @ 4K	•	*	*	*	0.11	0.25	0	.6 10.	5 0.05	0.27	0.5	3.5	
STD	12.5	SFTP @ UL		0.12	1.00	*	*	*	*	1	.3 14.	6 *	*	1.2	4.9		
@ UL			TIVE FAM	ILY 1	EVAPORATIVE FAMILY 2				EVA	PORAT	IVE FA	AMILY 3	E	EVAPORATIVE FAMILY 4			
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RI	ORV		2-D	RL	ORVR	
CERT	1.8	1.6	0.001	0.003	*	*	*	*	*	*	*	*	•	*	*	*	
STD	2.0	2.5	0.05	0.20	*	*	*	*	*	*	•	*		*	*		

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of June 2002.

Allen Lyons, Chief

Mobile Source Operations Division