## FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1108 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003:

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI YEA		TEST GROUP			VEHICLE TYPE C=passenger car; LDT=light-duty truck; DV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200		3FMXT04.01F6			LDT: 0-3,750 pounds LVW	LEV			100K / 100K	Gasoline (Tier 2 Unleaded)				
No.		EVAPORATIVE FAMILY (EVAF)			SPECIAL FEATURES EMISSION CONTROL SYSTE		* = not applicable	OC/T	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing WU= warm-up cat. O2S/HO2S=oxygen sensor/heate					
1	3FMXF	R015	5BBE	1	2TWC, TWC(2), 2HO2	S, HO2S, SFI,	AFS/	AFS/HAFS=air-fuel ratio sensor/heated AFS_EGR=exhaust						
2		*				÷	gas r	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
3		•				*	TBI≃							
4		*				*	dlagi							
EVAF No.							CLES SUBJECT TO SFTP ABBREVIATIONS:							
1	1 4.0				Ford Ranger Pickup 2WD									
*	* *		*		*									
*	*		+		*									
*			*		**************************************		*							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET NMOG @ RAF= * AVERAGE [g/mi] CH4 RAF = *			NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/ml]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram												
CER	CERT STD		NMOG	NMHC	NMHC STD	mg=millig	ot•soak K	L [g/mi]≖ru:	nning loss 1000 miles	ORVR	[g/gallor	ı dispensed]	on-board ros SFTP=supp	efueling vap	or recovery	g=gram	
0.05	3	0.062	CERT [g/mi]	CERT [g/mi]	[g/mi]	CO [g/mi]		NOx [g/mi]			HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]		
						CERT	STD	CERT	ST	) (	CERT	STD	CERT	STD	CERT	STD	
4.5	J. C.	@ 50K	0.065	*	0.075	1.1	3.4	0.04	0.2		1	15	*	*	0.05	0.3	
22.12	小坑	@ UL	0.087	*	0.090	1.6	4.2	0.1	0.3		1	18	*	*	0.1	0.4	
1	@ 50	°F & 4K	*	*	*	*	*	*	*		*	*	*	*	*	*	
@ 20		LEV) or 50K (Tier 1, TLEV)						O [g/mi] NMHC+N omposite) [g/mi] [US					NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50	50K		SFTP 2 = @ UL (Tier 1, TL		CERT	STD	CERT	STD	CERT	STD	CE	RT ST	CERT	STD	CERT	STD	
CERT	3.6			SFTP 1	*	*	*	*	0.02	0.14	0	4 8.0	0.04	0.20	0.1	2.7	
STD	10.0		10 T T.	SFTP 2	• 1	*	*	*	*	•		*	*	*	*	•	
@ UL			ATIVE FAM	AILY 1	EVAPORATIVE FAMILY 2 EVAPOR						DRATIVE FAMILY 3			EVAPORATIVE FAMILY 4			
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RI	ORV	₹ 3-D	2-D	RL	ORVR	
CERT	1.2	1.1	0.01	0.04	*	*	*	*	*	*		*	*	*	*	•	
STD	2.0	2.5	0.05	0.20	*	*	*	*	*	*	*	*	<b>-</b>	*	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 24TH day of July 2002.

Allen Lyons, Chief

Mobile Source Operations Division