## FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1110
New Passenger Cars, Light-Duty Trucks
and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP			VEHICLE TYPE PC=passenger car; LDT=light-duty MDV=medium-duty vehicle; LVW=l vehicle weight; ALVW=adjusted i	CATEGOR' vehicle; 1	EMISSION STAND. Y (LEV=low emis LEV= transitional LE\ LEV; SULEV=super U	sion /;	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200	3	3FMXT04.02F3		3	LDT: 3,751-5,750 pounds L\	ļ	LEV		100K / 100K	Gasoline (Indolene)				
No.		EVAPORATIVE FAMILY (EVAF)			SPECIAL FEAT EMISSION CONTROL		* = not applicable	OC	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust					
1	3FMXR0155BBE			1	2TWC, TWC(2),	2HO29	S, HO2S, SFI,	AF						
2	3FMXR0230BBE			2	2TWC, TWC(2), 2HO2S, HO2S, EGR, SFI, OBD (F)					gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger [CAC=charge air cooler OBD (F) / (P)=full /partial on-board				
3		*			•									
4		*				*		dia	diagnostic prefix 2=parallel (2) suffix=series					
EVAI No.				ICLES SUBJECT TO SFTP			BBREVIATIONS:							
1	1 4.0 Ford Ranger Pick					up 2WD/4WD; Mazda B4000 2WD/4WD								
1	2 4.0 Ford Explorer Sport 2W							D/4W	)/4WD					
2	2 2 4.0				Ford Explorer Sport Trac 2WD/4WD									
*	* *				•									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET N AVERAGE [g/mi]			NMOG @ RAF= 1.00 CH4 RAF = *		NMOG or nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D										1=2/3 day	
CER	CERT STD NMOG NMHC			NMHC	NMHC   dlurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refuelling vapor recovengemilligram mi=mile K=1000 miles F=degrees Fahrenheit SFTP=supplemental federal test									oor recovery derai test p	⁄g≃gram rocedure		
0.09	4 (	0.093	CERT [g/mi]	CERT [g/mi]	[g/mi]		[g/mi]	NO	x [g/mi]		НСНО	[mg/mi]		[g/mi]		x [g/mi]	
0.00						CERT	STD	CERT	ST	D	CERT	STD	CERT	STD	CERT	STD	
			0.052	*	0.100	1.1	4.4	0.1	0.4	4	1	18 *		*	0.04	0.5	
5 4 4			@ UL 0.074		0.130	1.6	5.5	0.1	0.	5	1	23	*	*	0.1	0.7	
	@ 50	0°F & 4K * *		*	*	*	*	•	*		*	*	*		*	•	
CO [ @ 20	g/mi] °F &	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)					(comp	g/mi] osite)		NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		MHC+NOx /mi] [SC03]	CO [g/mi] [SC03]		
50	50K		SFTP 2 = @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	SI	TD CE	RT ST	D CE	RT STD	CERT	STD	
CERT	4.3	6		SFTP 1	*	*	*	*	0.08	0.2	25 9	.3 10	.5 0.	07 0.27	0.1	3.5	
STD	12.5			SFTP 2	*	*	*	*	*	•	•	* *	-   ·	* *			
@ UL	Е	VAPOR	ATIVE FAN	IILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3					EVAPORATIVE FAMILY 4			
W OL	3-D	2-[	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RI	ORV	'R 3-	D 2-D	RL	ORVR	
CERT	1.2	1.3	0.01	0.16	0.8	1.5	0.002	0.02	*	*	*	*		•		*	
STD	2.0	2.5	0.05	0.20	2.0	2.5	0.05	0.20	*	*	*	*	*	*	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 18<sup>th</sup> day of July 2002.

Allen Lyons, Chief

Mobile Source Operations Division