

## FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1111
New Passenger Cars, Light-Duty Trucks
and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD	R	TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)			CATEGORY vehicle: T	EMISSION STANDA  (LEV=low emiss LEV= transitional LEV; LEV; SULEV=super ULE	ion	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)			
2003 3FMXT04.02F			A		LDT: 3,751-5,750 pounds LV		LEV		100K / 100K Gasoline (Tier 2 Unleaded)						
No.	FAM	AILY (E	N	ο.	SPECIAL FEATURES & *= not applic					OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S					
1	3FMXR0155BBE			Š	1	2TWC, TWC(2),	2HO25	, HO2S, SFI, (	MAT:	S/HAFS=air-fuel ratio s	ensor/heated AFS_FGD=avbauce				
2	3FMXR0230BBE				2	2TWC, TWC(2), 2H	02S, H	O2S, EGR, SE	-∥gas	gas recirculation AIR/PAIR=secondary air injection/pulsed   AIR MFI/SFI= multiport fuel injection/sequential MFI   TBI= throttle body injection TC/SC=turbo (euros absence					
3		*			3		*		TB						
4		*			4		*		CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series						
EVAI No.		ECS No.				VEHICLE MAKES & MODELS	VEI STA	HICLES SUBJI	ECT TO SFTP	ABBREVIATIONS:					
1_		1	4.0						a B40	000 2WD/4WD					
1_		2	4.0				Ford Explorer Sport 2WD/4WD								
2	2 4.0		$\Box$		Ford Explorer Sport Trac 2WD/4WD										
*		*	*	$\Box$	*										

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET N AVERAGE [g/mi]				NMOG @ RAF= * CH4 RAF = *								CH4 hydroca RAF=reacti				
CER	0.004		NMOG NMHC		NMHC	mg=millig	Ot-Soak K	c [8/m]-ru	nning los 1000 mile:	SUR	vik (g/galio	n dispensed] Fahrenheit	=on-board r SFTP=supp	efueling var	or recovery	q=qram
0.094			CERT [g/mi]	CERT	[g/mi]		[g/mi]		Ox [g/mi		HCHO	[mg/mi]	PM [g			x [g/mi]
The state of				1.52	<del> </del>	CERT	STD	CER.	r s	D	CERT	STD	CERT	STD	CERT	STD
5		@ 50K	0.033 *		0.100	0.5	4.4	0.04	0.	.4	*	18	*	*	0.1	0.5
			0.049	*	0.130	0.7	5.5	0.1	0.	0.5		23	*	•	0.1	0.7
	@ 50°	F & 4K	*	*	*	*	•	*	7		*	*	*	•	*	*
@ 20		LE		ler 1, TLEV)	NMHC+NC (compo	osite)	) (composite)		NMHC+N( [g/mi] [US				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
50	N.	SFIFZ	= @ UL (Tie	r 1, ILEV)	CERT	STD	CERT	STD	CERT	S	TD CE	RT STI	D CERT	STD	CERT	STD
CERT	1.9	1.1	4. 数多	SFTP 1	*	*	*	*	0.06	0.	25 5	i.6 10.	5 0.05	0.27	0.1	3.5
STD	12.5	10 m		SFTP 2	*	*	*	*	*		*	• •	*	*	*	*
@ UL			ATIVE FA	VILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
_	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-[	R	L ORVI		2-D	RL	ORVR
CERT	1.2	1.3	0.01	0.16	0.8	1.5	0.002	0.02	*	*	*		*	+	*	*
STD	2.0	2.5	0.05	0.20	2.0	2.5	0.05	0.20	*	*	*	*	*	+	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 2474 day of October 2002.

Allea Lyons, Chief

Mobile Source Operations Division