FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1119
New Passenger Cars, Light-Duty Trucks
and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD				M	VEHICLE TYPE C=passenger car; LDT=light-duty truck; DV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas					
200			T04.62F7		LDT: 3,751-5,750 pounds LVW		LEV		100K / 100K	Gasoline (Tier 2 Unleaded)					
No.	FAMI	VAPORATIVE AMILY (EVAF)				SPECIAL FEATURES & EMISSION CONTROL SYSTEMS (ECS) * = not applicable				cat. ADSTWC=adsorbing TWC IO2S=oxygen sensor/heated O2S					
1	3FMXI	MXR0160BBE			2TWC, TWC, 2HO2S(2), EGR, SFI, C	AFS/I	HAFS=air-fuel ratio s	ensor/heated AFS_EGR=avhaue+						
2		*		2	*	······································	—∥gas r	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo (super charge)							
3		*		3	*		TBI=								
4		*		4			diagn	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parailel (2) suffix=series							
EVAF No.	,	cs o.	ENGINE SIZE (L)		VEHICLE VEH MAKES & MODELS STAP	HICLES SUBJECT TO SFTP			BBREVIATIONS:						
1	11	1	4.6		Ford Explorer 2WD/4WD; Mercury Mountaineer 2WD/4WD										
*		*	*												
*	*	*	*				*								
*	*		*	-											

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]		EET g/mi]	NMOG @ RAF= * CH4 RAF = *		NMOG or							H4 hydroca RAF=reactiv					
CER	T	STD NMO		NMHC	NMHC STD [g/mi]	mg=millig	or-soan in	- լցուոյ–ւս	nning loss 1000 miles	OKVK	g/gallor	i aispensea)	≖on-board ı	efueling var plemental fe	or recovery	g=gram	
0.09	0.094		CERT [g/mi]	CERT [g/mi]			[g/mi]	NO	x [g/mi]	F	нсно	mg/mi]		g/mi]		x [g/mi]	
			[8,111]	[8,111]		CERT	STD	CERT	ST	D C	ERT	STD	CERT	STD	CERT	STD	
7.33	4 5 5	@ 50K	0.059	*	0.100	1.0	4.4	0.05	0.4		0.4	18	*	*	0.03	0.5	
		@ UL	0.076	*	0.130	1.1	5.5	0.1	0.5	5	1	23	*	*	0.1	0.7	
	@ 50°	F & 4K	*	*	*	•	*	*	*		*	*		*	*	*	
CO [@ 20	°F&	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			NMHC+NOx [g/mi] (composite)		CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]			CO [g/mi] [US06]	NMHC+NOx [g/mi] [SC03]		CO [g/mi]		
50	K	SFTP 2 = @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	STD	CE				CERT	STD		
CERT	1.9	1.4	" "	SFTP 1	*	*	*	*	0.03	0.25	8.				0.3	3.5	
STD	12.5	34.1		SFTP 2	*	*	*	*	*	*	-		*	*	*	+	
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				F	EVAPORATIVE FAMILY 4			
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL				· · · · · · · · · · · · · · · · · · ·		
CERT	1.2	1.3	0.01	0.16	*	*	*	*	*	*	1	ORVE	3-0	2-D	RL	ORVR	
STD	2.0	2.5	0.05	0.20	*	*	*	-	*	*	 .	-			 	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 23 P2 day of September 2002.

Allen Lyons, Chief

Mobile Source Operations Division