

DAIMLERCHRYSLER CORPORATION

EXECUTIVE ORDER A-009-0577-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD		TEST GROUP			VEHICLE TYPE PC=passenger car; LDT=light-dui MDV=medium-duty vehicle; LVW= vehicle weight; ALVW=adjusted	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; TLEV= transitional LEV; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)					
200		3CRXT02.42D0		0	LDT: 3,751-5,750 pounds L	LEV			100K / 100K Gasoline						
No.			ORATIVE Y (EVAF)				SPECIAL FEA EMISSION CONTROL		* = not applicable	OC	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing				
1	3CRX	(R017	7GCA	1			, SFI, OBD (F)	Ar	S/HAFS=air-fuel ratio s	IO2S=oxygen sensor/heated O2S ensor/heated AFS EGR=exhaust					
2		*			*					gas recirculation AIR/PAIR=secondary air injection/pulsec AIR MFI/SFI= multiport fuel injection/sequential MFI					
3		*		3		*				TBI= throttle body injection TC/SC=turbo /super charger					
4		*		4		. *	T W	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series							
EVAF No.			ENGIN SIZE (L		VEHICLE MAKES & MODELS		HICLES SUBJECT TO SFTP NDARDS ARE UNDERLINED			ABBREVIATIONS:					
1	1 2		2.4		Chrysler Voyager, Dodge Caravan, Chrysler Caravan										
1_		1 2.4			Chrysler Voyager, Dodge Caravan, Chrysler Caravan										
*		*	*		*										
*	* *			196.			*								

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NM AVE	NMOG FLEET N AVERAGE [g/mi]			NMOG @ RAF=0.94 CH4 RAF = *									rbon CO=ca			
CER	CERT STD		NMOG	NMHC	NMHC STD	mg=millig	resour ite	- (g/iiij-rui	nning loss 1000 miles	UKVK	. Įg/ga⊪or	i aispensed!	=on-board re	fuelinα vap	Or recovery	a=aram
0.08	5	0.093	CERT [g/mi]	CERT [g/mi]	[g/mi]		CO [g/mi]		x [g/mi]		нсно (mg/mi]	PM [g	/mi]	deral test procedure Hwy NOx [g/mi]	
A STATE OF THE STA	102012		[8,,,,,,]			CERT	STD	CERT	ST	D 0	CERT	STD	CERT	STD	CERT	STD
		@ 50K	0.047	*	0.100	2.2	4.4	0.1	0.4	4	2	18	*	*	0.02	0.5
	167	@ UL	0.047	*	0.130	2.2	5.5	0.1	0.9	5	2	23	*	*	0.02	0.7
2. di	@ 50	°F & 4K	*	*	*	*	*	*	*		•	*	*	*	*	*
@ 20	@ 20°F & 🖟 L		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			NMHC+NOx [g/mi] CO [g/mi (composite) (composit			NMHC+NOx CO [g/mi] [g/mi] [US06] [US06]			NMHC+NOx [q/mi] [SC03]		CO [g/mi] [SC03]		
50			= @ UL (Tier 1, TLEV)		CERT	STD	CERT	STD	CERT	STD	CE			STD	CERT	STD
CERT	3.4			SFTP 1	*	*	*	*	0.02	0.25	5 0.	5 10.	0.04	0.27	0.4	3.5
STD	12.5		10 E 17	SFTP 2	*	*	*	*	*	*	*		•	•	*	•
@ UL		VAPOR.	ATIVE FAM	IILY 1	EVAPORATIVE FAMILY 2			EVAPORATIVE FAMILY 3				EV	EVAPORATIVE FAMILY 4			
	3-D	2-[) RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVE		2-D	RL	ORVR
CERT	0.8	3.0	0.001	0.03	*	*	*	*	*	*	*	*	*	+	*	*
STD	2.0	2.5	0.05	0.20	*	*	*	*	*	*	*	-	*	*	+	*

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order. This Executive Order hereby supersedes Executive Order A-009-0577 dated July 1, 2002.

Executed at El Monte, California on this ______ day of November 2002.

Allen Lyons, Chief

Mobile Source Operations Division