

DAIMLERCHRYSLER CORPORATION

EXECUTIVE ORDER A-009-0578 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

	MODEL TEST GROUP			M	VEHICLE TYPE C=passenger car; LDT=light-duty truck DV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW)	CATEGOR vehicle;	EMISSION STANDAY (LEV=low emis FLEV= transitional LEV LEV; SULEV=super UL	sion EVAPORATIVE	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)					
200	2003 3CRXT03.32I				LDT 3,751-5,750 pounds LVW		LEV	100K / 100K	Flexible Fuel: Ethanol (E85) / Gasoline					
No.	FAM	PORA IILY (E	VAF)	No.	SPECIAL FEATURES EMISSION CONTROL SYST	S & 'EMS (ECS)	* = not applicable	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing WU= warm-up cat. O2S/HO2S=oxygen sensor/heate						
1	3CR>	CRXR0177XAA			H02S(2), TW	C, SFI, OBD (F)	AFS:MAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger							
2		*				*								
3		*				*								
4		*		4		*	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series							
EVÁI No.	_	ECS ENGINE No. SIZE (L)					ECT TO SFTP E UNDERLINED	ABBREVIATIONS:						
1	1 3.3			Dodge Caravan, Chrysler Voyager/Town & Country, Chrysler Caravan										
*	* *			*										
*		* *			*									
*	*		*				*							

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

AVER	G FLEE		IOG @ RA CH4 R	F=0.73 (0.94) AF = *	NMOG	murogen	nunu=tor	maidenvde	PM≅nam	iciliate m:	latter	RAFEreseth	rbon CO=ca	at factor '	2/2 D [~/+~~+	1-2/2 4	
CER	T STI	2	NMOG NMHC		NMHC	diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram mg=mill(gram mi=mile K=1000 miles F=degrees Fahrenheit SFTP=supplemental federal test procedure											
0.08	5 0.09	3	CERT [g/mi]	CERT [g/mi]	STD	CO [g/mi]			NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]		
	A CONTRACTOR OF THE CONTRACTOR			[9/1111]	[g/mi]	CERT	STD	CERT		CE	ERT	STD	CERT	STD	CERT	STD	
	@ 5	OK	0.036 (0.074)		(0.100	1.0 (1.3)		4.4 0.2	0.4		3	18	*	*	0.1	0.5	
			0.036		0.130	1.0	(4.4) 5.5	0.2	(0.4)		(2)	(18)			(0.1)	(0.5)	
1	@		(0.074)	*	(0.200)	(1.3)	(5.5)	(0.2)	(0.5)		(2)	23 (23)	*	*	0.1 (0.1)	0.7 (0.7)	
	@ 50°F	& 4K	*	*	*	*	*	*	*		*	*	*	*	*	*	
CO [@ 20	°F&	LE'	LEV) or 50K (Tier 1, TLEV)			NMHC+NOx [g/mi] CO [g (composite) (compo			NMHC+NOx [g/mi] [US06]					IC+NOx	CO [g/mi] (SC03)		
50		SFTP 2 =	@ UL (Tier	1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CE	RT ST	CERT	STD	CERT	STD	
CERT	6.1 (7.8)		展養	SFTP 1	*	*	*	*	(0.08)	(0.25)	(0.	6) (10.	5) (0.04)	(0.27)	(0.3)	(3.5)	
STD	12.5 (12.5)		4	SFTP 2	*	*	*	*	*	*	•	*		•	*	*	
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EV				EVAP	VAPORATIVE FAMILY 3			ΕV	EVAPORATIVE FAMILY 4			
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV	R 3-D	2-D	RL	ORVR	
CERT	1.7 (1.2)	1.5 (0.9)	0.000		*	*	*	*	*	*	*	*	*	*	*	*	
STD	2.0 (2.0)	2.5 (2.5)	0.05 (0.05)	0.20 (0.20)	•	•	*	*	*	*	•	•	*	*	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this $2^{\mu D}$

Allen Lyons, Chief

Mobile Source Operations Division

day of July 2002.