

DAIMLERCHRYSLER CORPORATION

EXECUTIVE ORDER A-009-0582 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD	AR .	TEST GROUP			ME	VEHICLE TYPE =passenger car; LDT=light-duty truck; V=medium-duty vehicle; LVW=loaded ehicle weight; ALVW=adjusted LVW)	CATEG	le; TLEV= transitional LEV tra LEV; SULEV=super UL	sion :	EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
200	13	3CRXT03.72Z0		Ü		LDT: 3,751-5,750 pounds LVW		ed as ARB LEV I ULE\	/	100K / 100K	Gasoline (Indolene)				
No.		VAPORATIVE AMILY (EVAF)		N	р.	SPECIAL FEATURES EMISSION CONTROL SYST		* = not applicable	O W	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC WU= warm-up cat. O2S/HO2S=oxygen sensor/heated O2S					
1	3CR	3CRXR0155GCH				2WUOC, TWC, SF	, 2H02S(2),	B A	AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAR=secondary air injection/pulsed AIR MF/JSFi= multiport fuel injection/sequential MF/JSFi= multiport fuel injection/sequential MF/JSFi= TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / [P]=full /partial on-board diagnostic prefix 2=parallel (2) suffix-series						
2		*			╗		•	- I ga							
3		*					*	Ţ							
4		*					*	- di							
EVA No.		ECS ENGINE VEHICLE VEHICLES SUBJECT No. SIZE (L) MAKES & MODELS STANDARDS ARE U			ABBREVIATIONS:										
1	1 3.7				Jeep Liberty 2WD/4WD										
***	• • •														
*							•								
*		•													

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]			NMOG @ RAF=* CH4 RAF = *				CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refuelling vapor recovery g=gram											
CERT STD		STD	NMOG		NMHC	NMHC STD	mg=millig	ram mi=	∟ [g/mi]≖rui ≔mile K=1	ining loss 000 miles	F=	K (g/galloi :degrees F	n dispensed ahrenheit	on-board SFTP=sup	efueling vap plemental fe	or recovery deral test pi	g=gram rocedure	
0.09	5 0.093		CERT		CERT	[g/mi]		[g/mi]	NC	NOx [g/mi]		НСНО	[mg/mi]	PM [Hwy NO		
				ו ו	[g/mi]		CERT	STD	CERT	ST	D	CERT	STD	CERT	STD	CERT	STD	
		@ 50K	0.049		•	0.100 1.1		3.4	0.1	0.2	0.2 1		15	•	*	0.01	0.27	
	14.3	@ UL	0.049		*	0.130	1.1	4.2	0.1	0.:	3	1	18	*	*	0.01	0.40	
1	@ 50°		& 4K *		*	*	*	•	*	*		*	*	*	*	*	•	
	[g/mi])°F &	SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)						g/mi] posite)		NMHC+NOx [g/mi] [US06]				HC+NOx ni] [SC03]	CO [g/mi] [SC03]			
50K		SFTP 2 = @ UL (Tier		Tier 1, T	LEV)	CERT	STD	CERT	STD	CERT	ST	D CE	RT ST	D CER	T STD	CERT	STD	
CERT	5.0		e in the	SFTP	@ 4K	*	*	*	*	0.06	0.2	25 1	.9 10.	5 0.09	0.27	0.4	3.5	
STD	12.5			SFTP	@ UL	0.15	1.04	*	*	*	*	2	.2 14.	6 .	•	0.6	4.9	
@ UL	EVAPORATIVE FAMILY 1					EVAPORATIVE FAMILY 2				EVA	EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
	3-D	2-0) F	₹L	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RI	ORV	R 3-D	2-D	RL	ORVR	
CERT	1.1	0.7	0.0	001	0.06	*	*	*	*	*	*	*	*	*	*	*		
STD	2.0	2.5	0.	.05	0.20	*	*	*	*	*	*	*	*	*		•	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models have been certified on the condition that the manufacturer provide all on-board diagnostic demonstration data required by 13 CCR Section 1968.1(g) by August 1, 2002. Failure to submit the required demonstration data by the specified date, or failure of the submitted demonstration data to show compliance with the test procedures, shall be cause for the Air Resources Board to revoke this Executive Order and vehicles sold under the revoked conditional certification shall be deemed uncertified.

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 2014 day of June 2002.

Allen Lyons, Chief

Mobile Source Operations Division