		-	_	_										· g				
	72	-	- 1		_	-	-	-		-	-	-	-		-		_	
· ·		-	Δ				C	n	11	D	r		<b>C</b>	D	n		D	n
-		-	~	811		کا ا	3	J	U	п	ີ			D	J	м	m	U

DAIMLERCHRYSLER CORPORATION

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

YEA	MODEL YEAR TEST GROUP			N	VEHICLE TYPE C=passenger car; LDT=light-duty DV=medium-duty vehicle; LVW=l vehicle weight; ALVW=adjusted L	truck; CATEGOF baded vehicle; VW) ULEV=uitra	EMISSION STANE (LEV=low em TLEV= transitional LE LEV; SULEV=super L	ssion V:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
2003 3CRXT03.92D0				ו	LDT: 3,751-5,750 pounds LV	w	LEV		100K / 100K	Gasoline			
No.	EVAPORATIVE FAMILY (EVAF)			MILY (EVAF) No. EMISSION CONTROL SYSTE			* = not applicabl	cat. ADSTWC=adsorbing TWC					
1	3CRX	(R015	5GCH	1	2WUOC, 2HC	02S(2), TWC, SFI, O	AFS	S/HAFS=air-fuel ratio s	IO2S=oxygen sensor/heated O2S ensor/heated AFS EGR=exhaust				
2		*		2		*		—gas	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI				
3		*	*			*	ТВ	TBI= throttle body injection TC/SC=turbo /super charger					
4		*		4		*	dia	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series					
EVAF No.		CS No.	ENGINE SIZE (L		VEHICLE MAKES & MODELS	VEHICLES SUB STANDARDS AF	JECT TO SFTP	Ll	ABBREVIATIONS:				
1		1	3.9		Dodge Dakota Pickup								
*		*	*										
*		*	*		······································								
*		* *											

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]				) RAF=0.94 RAF = *	NMOG or								urbon CO=c vity adjustm			
CER	T	STD	NMOG NMHC		NMHC STD	diurnal+f	oc oount it	- [g/mi]-/u	nning los: 1000 miles		c (g/ganor	n dispensed ahrenheit	j=on-board r	efueling var	or recovery	a=aram
0.08	5	0.093	CERT [g/mi]	CERT [g/mi]	[g/mi]		[g/mi]	NC	Dx [g/mi]			[mg/mi]	PM [	plemental fe g/mi]		rocedure  x [g/mi]
A CONTRACTOR OF	ALC: NO.					CERT	STD	CER	r st	D	CERT	STD	CERT	STD	CERT	STD
67 B	@ 50K		0.058	*	0.100	1.4	4.4	0.2	0.	4	1	18	*	*	0.1	0.5
	7.2	@ UL	0.058	+	0.130	1.4	5.5	0.2	0.	5	1	23	*	*	0.1	0.7
	@ 50	0°F & 4K	*	*	*	*	*	+			*	*	*	*	*	*
@ 20	@ 20°F & 🚺 LEV) o			K (SULEV, ULEV, NMHC+NO 50K (Tier 1, TLEV) (compo L (Tier 1, TLEV) CFRT			osite) (composite)			NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		[g/mi] C03]
<u> </u>				1,1227)	CERT	STD	CERT	STD	CERT	STD	)   CE	RT ST	D CER	T STD	CERT	STD
CERT	8.1		- Mar 1	SFTP 1	•	•	*	*	*	*		*	*	*	*	*
STD	12.5			SFTP 2	*	*	*	*	*	*		· +	*	*	+	*
@ UL						EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4		
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL			2-D		
CERT	1.1	0.7	0.00	0.03	*	*	*	*		*			× 3-0	2-0	RL	ORVR
STD	2.0	2.5	0.05	0.20	*	*	*	*	*	*	+				<u> </u>	

**BE IT FURTHER RESOLVED**: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

**BE IT FURTHER RESOLVED:** That the listed vehicle models have been certified on the condition that the manufacturer provides all on-board diagnostic demonstration data required by 13 CCR Section 1968.1(g) by August 1, 2002. Failure to submit the required demonstration data by the specified date, or failure of the submitted demonstration data to show compliance with the test procedures, shall be cause for the Air Resources Board to revoke this Executive Order and vehicles sold under the revoked conditional certification shall be deemed uncertified.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of July 2002.

ephal Sumour Allen Lyons, Chief Mobile Source Operations Division