

## **DAIMLERCHRYSLER CORPORATION**

EXECUTIVE ORDER A-009-0588 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

	MODEL TEST GROU				VEHICLE TYPE PC=passenger car; LDT=light-dut MDV=medium-duty vehicle; LVW= vehicle welght; ALVW=adjusted	CATEGOR\ vehicle; T ULEV=ultra I	LEV= transitional LE\ .EV; SULEV=super UI	sion /:	EXHAUST / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)				
200		3CRXT04.02Z0			LDT: 3,751-5,750 pounds L	1) USEPA B 2) Counted	in 9 as ARB LEV I ULE <sup>v</sup>	,	100K / 100K	Gasoline (Indolene)				
No.		EVAPORATIVE FAMILY (EVAF)		No	SPECIAL FEAT EMISSION CONTROL	L FEATURES & *= not applical			OC	DC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing VU= warm-up cat. O2S/HO2S=oxygen sensor/heated				
1	3CRXI	CRXR0155GCH					2H02S(2), OB	AF	S/HAFS=air-fuel ratio s	ensor/heated AFS_EGR=exhaust				
2		*		2		*			—  ga Δι	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI				
3		•						−Птв	TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series					
4						*		dia						
EVAF No.	1 -	CS lo.	ENGIN SIZE (L		VEHICLE MAKES & MODELS			CT TO SFTP UNDERLINED	ABBI	REVIATIONS:				
1	1 4.0			Jeep Grand Cherokee 2WD/4WD										
*	*   *													
*	1	*	*		*									
*	* * *							*						

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	NMOG FLEET NMOG @ RAF= AVERAGE [g/mi] CH4 RAF = *				NMOG or	CH4=methane NMOG=non-CH4 organic gas NMHC=non-CH4 hydrocarbon CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/test]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram													
	0.085 0.093 CER [g/mi		NMOG NM		NMHC	mg=millig	ot-soak K	∟ [g/mi]=rui	nning loss 000 miles	ORV	R [g/gallor	n dispensed ahrenheit	]≖on-board r	efueling vap piemental fe	or recovery	g≃gram			
			0.093	[g/mi]		CERT [g/mi]	[g/mi]	CO [g/mi]			x [g/mi]	g/mi] HCHO		[mg/mi]	PM [g/mi]		Hwy NOx [g/mi]		
						[8,114]	10 1	CERT	STD	CERT	ST	D	CERT	STD	CERT	STD	CERT	STD	
4	@ 50K		0.06	8	*	0.100	1.7	3.4	0.1	0.2	2	1	15	*	*	0.02	0.27		
			@ UL	0.06	8	*	0.130	1.7	4.2	0.1	0.:	3	1	18	*	*	0.02	0.40	
		@ 50°	F & 4K	*		*	*	*	*	*	*		*	*	*	*	•	*	
	O [g	/mi] F &	LEV) or 50K (Tier 1, TLEV)						g/mi] osite)					NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC031			
	50K		SFTP 2 = @ UL (Tier 1,		, TLEV)	CERT	STD	CERT	STD	CERT	ST	D CE	RT ST			CERT	STD		
CE	RT	5.4			SF	TP @ 4K	*	*	*	*	0.06	0.2	5 1	4 10.	5 0.06	0.27	0.1	3.5	
S	TD	12.5	1,000		SF	TP@UL	0.22	1.04	*	*	*	*	4	.2 14.	6 *	*	1.6	4.9	
@	UL -		VAPOR		<del></del>		EVAPORATIVE FAMILY 2				EVA	PORA	TIVE FA	MILY 3	E	EVAPORATIVE FAMILY 4			
L		3-D	2-[		RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	. ORV	R 3-D	2-D	RL	ORVR	
$\vdash$	RT	1.1	0.7	7 0	.001	0.03	*	*	*	*	*	*	•	*	*	•	*	*	
ST	D	2.0	2.5	5 (	0.05	0.20	*	*	*	*	*	*	*	*		+ +	·	<del>  •  </del>	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

**BE IT FURTHER RESOLVED:** That the listed vehicle models have been certified on the condition that the manufacturer provide all on-board diagnostic demonstration data required by 13 CCR Section 1968.1(g) by August 1, 2002. Failure to submit the required demonstration data by the specified date, or failure of the submitted demonstration data to show compliance with the test procedures, shall be cause for the Air Resources Board to revoke this Executive Order and vehicles sold under the revoked conditional certification shall be deemed uncertified.

**BE IT FURTHER RESOLVED:** That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of July 2002.

Allen Lyons, Chief

Mobile Source Operations Division